Model: EN-O24100-RB2-T

InvisiLED® Electronic Remote Transformer

WAC LIGHTING

Responsible Lighting®



Fixture Type:	
Catalog Number:	
Project:	
Location:	

PRODUCT DESCRIPTION

Low Voltage electronic transformer designed to be used as an enclosed remote transformer. Enclosure has separate compartments for transformer, line and low voltage wiring. Transformer may be safely loaded to 100% of stated capacity.

FEATURES

- U.L. 2108 listed electronic low voltage transformer.
- · Class 2 rated.
- Built-in auto reset, soft start, short and overload circuit protection features. Soft start delayed start feature extends lamp life.
- In the case of a system overload or short circuit the transformer will
 revert to a "hold" position and then automatically reset the system when
 the problem is solved. System protection is designed to last several hours.

SPECIFICATIONS

Max Load: 96W Min Load: 1W

Input: 120-277VAC 0.95A 50/60Hz

Output: 24V DC 4A Max

Standards: Wet location. UL & CUL Listed

Ambient Temperature: -4°F to 113°F (-20°C to 45°C)

Dimming: 0 - 10V

ORDER NUMBER

Model	Output	L	W	Н
EN-O24100-RB2-T	24V, 96W	117/16"	41/8"	1 15/16"

EN-O24100-RB2-T