

Project:
Location:
Fixture Type:
Catalog Number:



Lightstick

WS-47919

PRODUCT DESCRIPTION

Modern and ultra-minimal. Lightstick is a slim LED vanity luminaire designed perfectly for residential, hospitality and commercial powder rooms. A slender bar of light constructed froma co-extrusion of clear and white acrylic affords the luxurious dimensional look of cased glass but durable enough for its dramatic proportions. The versatile design allows it to beplaced horizontally or vertically or even at angles on walls and ceilings.

FEATURES

- ACLED driverless technology
- Co-extruded acrylic diffuser
- 1" slim junction box included and can be ordered separately (model# JB-0501)
- Conversion plate included for 4" junction box

SPECIFICATIONS

Rated Life	54000 Hours
Standards	ETL, cETL,Damp Location Listed,Title 24 JA8: 2019 Compliant
Input	120 VAC,50/60Hz
Dimming	ELV
Mounting	Can be mounted on ceiling or wall in all orientations
Color Temp	3000K
CRI	90
Construction	Aluminum hardware, co-extruded acrylic diffuser

WS-47919

REPLACEMENT PARTS

JB-0501 - 1" Slim Junction Box

Model & Size Color	Temp Finish	LED Watts LED Lur	mens Delivered Lumens
WS-47919 19" 3000K		uminum 16.8W 1268 16.8W 1268	975 975

Example: WS-47919-WT

25" ______ 2" _____ 1½'

Project:	
Location:	
Fixture Type:	
Catalog Number:	

AVAILABLE FINISHES:



Lightstick

WS-47925

PRODUCT DESCRIPTION

Modern and ultra-minimal. Lightstick is a slim LED vanity luminaire designed perfectly for residential, hospitality and commercial powder rooms. A slender bar of light constructed froma co-extrusion of clear and white acrylic affords the luxurious dimensional look of cased glass but durable enough for its dramatic proportions. The versatile design allows it to beplaced horizontally or vertically or even at angles on walls and ceilings.

FEATURES

- ACLED driverless technology
- Co-extruded acrylic diffuser
- 1" slim junction box included and can be ordered separately (model# JB-0501)
- Conversion plate included for 4" junction box

SPECIFICATIONS

Rated Life	54000 Hours
Standards	ETL, cETL,Damp Location Listed,Title 24 JA8: 2019 Compliant
Input	120 VAC,50/60Hz
Dimming	ELV
Mounting	Can be mounted on ceiling or wall in all orientations
Color Temp	3000K
CRI	90
Construction	Aluminum hardware, co-extruded acrylic diffuser

WS-47925

REPLACEMENT PARTS

JB-0501 - 1" Slim Junction Box

Model & Size	Color Temp Fi	inish	LED Watts	LED Lumens	Delivered Lumens
	3000K 3000K	/ LE DI GOTTE G / (1 GTTTTT G TTT	22.4W 22.4W	1708 1708	1375 1375

Example: WS-47925-WT



Project:
Location:
Fixture Type:
Catalog Number:



Lightstick

WS-47937

PRODUCT DESCRIPTION

Modern and ultra-minimal. Lightstick is a slim LED vanity luminaire designed perfectly for residential, hospitality and commercial powder rooms. A slender bar of light constructed froma co-extrusion of clear and white acrylic affords the luxurious dimensional look of cased glass but durable enough for its dramatic proportions. The versatile design allows it to beplaced horizontally or vertically or even at angles on walls and ceilings.

FEATURES

- ACLED driverless technology
- Co-extruded acrylic diffuser
- 1" slim junction box included and can be ordered separately (model# JB-0501)
- Conversion plate included for 4" junction box

SPECIFICATIONS

Rated Life	54000 Hours
Standards	ETL, cETL,Damp Location Listed,Title 24 JA8: 2019 Compliant
Input	120 VAC,50/60Hz
Dimming	ELV
Mounting	Can be mounted on ceiling or wall in all orientations
Color Temp	3000K
CRI	90
Construction	Aluminum hardware, co-extruded acrylic diffuser

WS-47937

REPLACEMENT PARTS

JB-0501 - 1" Slim Junction Box

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-47937 37"	3000K	AL Brushed Aluminum	33.2W	2450	1949
	3000K	WT White	33.2W	2450	1949

Example: WS-47937-WT



1 Tojece.
Location:
Fixture Type:
Catalog Number:

Project:



Lightstick

WS-47949

PRODUCT DESCRIPTION

Modern and ultra-minimal. Lightstick is a slim LED vanity luminaire designed perfectly for residential, hospitality and commercial powder rooms. A slender bar of light constructed froma co-extrusion of clear and white acrylic affords the luxurious dimensional look of cased glass but durable enough for its dramatic proportions. The versatile design allows it to beplaced horizontally or vertically or even at angles on walls and ceilings.

FEATURES

- ACLED driverless technology
- Co-extruded acrylic diffuser
- 1" slim junction box included and can be ordered separately (model# JB-0501)
- Conversion plate included for 4" junction box

SPECIFICATIONS

Rated Life	54000 Hours
Standards	ETL, cETL,Damp Location Listed,Title 24 JA8: 2019 Compliant
Input	120 VAC,50/60Hz
Dimming	ELV
Mounting	Can be mounted on ceiling or wall in all orientations
Color Temp	3000K
CRI	90
Construction	Aluminum hardware, co-extruded acrylic diffuser

WS-47949

REPLACEMENT PARTS

JB-0501 - 1" Slim Junction Box

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-47949 49"	3000K	AL Brushed Aluminum	44W	3171	2479
	3000K	WT White	44W	3171	2479

Example: WS-47949-WT



i roject.	
Location:	
Fixture Type:	
Catalog Number:	

Project.



Lightstick

WS-47961

PRODUCT DESCRIPTION

Modern and ultra-minimal. Lightstick is a slim LED vanity luminaire designed perfectly for residential, hospitality and commercial powder rooms. A slender bar of light constructed froma co-extrusion of clear and white acrylic affords the luxurious dimensional look of cased glass but durable enough for its dramatic proportions. The versatile design allows it to beplaced horizontally or vertically or even at angles on walls and ceilings.

FEATURES

- ACLED driverless technology
- Co-extruded acrylic diffuser
- 1" slim junction box included and can be ordered separately (model# JB-0501)
- Conversion plate included for 4" junction box

SPECIFICATIONS

Rated Life	54000 Hours
Standards	ETL, cETL,Damp Location Listed,Title 24 JA8: 2019 Compliant
Input	120 VAC,50/60Hz
Dimming	ELV
Mounting	Can be mounted on ceiling or wall in all orientations
Color Temp	3000K
CRI	90
Construction	Aluminum hardware, co-extruded acrylic diffuser

WS-47961

REPLACEMENT PARTS

JB-0501 - 1" Slim Junction Box

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-47961 61"	3000K	AL Brushed Aluminum	45.9W	3651	2826
	3000K	WT White	45.9W	3651	2826

Example: WS-47961-WT

Project:	
Location:	
Fixture Type:	

AVAILABLE FINISHES:

Catalog Number:



Lightstick

WS-47973

PRODUCT DESCRIPTION

Modern and ultra-minimal. Lightstick is a slim LED vanity luminaire designed perfectly for residential, hospitality and commercial powder rooms. A slender bar of light constructed froma co-extrusion of clear and white acrylic affords the luxurious dimensional look of cased glass but durable enough for its dramatic proportions. The versatile design allows it to beplaced horizontally or vertically or even at angles on walls and ceilings.

FEATURES

- ACLED driverless technology
- Co-extruded acrylic diffuser
- 1" slim junction box included and can be ordered separately (model# JB-0501)
- Conversion plate included for 4" junction box

SPECIFICATIONS

Rated Life	54000 Hours
Standards	ETL, cETL,Damp Location Listed,Title 24 JA8: 2019 Compliant
Input	120 VAC,50/60Hz
Dimming	ELV
Mounting	Can be mounted on ceiling or wall in all orientations
Color Temp	3000K
CRI	90
Construction	Aluminum hardware, co-extruded acrylic diffuser

WS-47973

REPLACEMENT PARTS

JB-0501 - 1" Slim Junction Box


Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-47973 73"	3000K	AL Brushed Aluminum	66W	4900	3782
	3000K	WT White	66W	4900	3782

Example: WS-47973-WT

Project:	
Location:	
Fixture Type:	

Catalog Number:

D.--!---



Lightstick

WS-47997

PRODUCT DESCRIPTION

Modern and ultra-minimal. Lightstick is a slim LED vanity luminaire designed perfectly for residential, hospitality and commercial powder rooms. A slender bar of light constructed froma co-extrusion of clear and white acrylic affords the luxurious dimensional look of cased glass but durable enough for its dramatic proportions. The versatile design allows it to beplaced horizontally or vertically or even at angles on walls and ceilings.

FEATURES

- ACLED driverless technology
- Co-extruded acrylic diffuser
- 1" slim junction box included and can be ordered separately (model# JB-0501)
- Conversion plate included for 4" junction box

SPECIFICATIONS

Rated Life	54000 Hours
Standards	ETL, cETL,Damp Location Listed,Title 24 JA8: 2019 Compliant
Input	120 VAC,50/60Hz
Dimming	ELV
Mounting	Can be mounted on ceiling or wall in all orientations
Color Temp	3000K
CRI	90
Construction	Aluminum hardware, co-extruded acrylic diffuser

WS-47997

REPLACEMENT PARTS

JB-0501 - 1" Slim Junction Box

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-47997 97"	3000K	AL Brushed Aluminum	88W	6342	4874
	3000K	WT White	88W	6342	4874

Example: WS-47997-WT