

# WAC LIGHTING

## Low Voltage ME-808

### LED MR16 Display Spot Light 3000K

Model & Wattage

Finish

ME-808 50W  
ME-808LED 8W

BK Black  
WT White

Example: **ME-808-BK**

#### DESCRIPTION

Single Spot Light with electronic transformer. Engineered with an integral transformer and designed for mounting to walls or ceilings, low and line voltage Display Spot Lights deploy optimal accent lighting from surface mounted canopies that can be custom designed with any of WAC low voltage track heads.

#### FEATURES

- Integral electronic transformer
- Accepts 12V LED MR16, Halogen MR16 lamps up to 50W max
- LED MR16 included when ordered as LED
- 1 watt minimum load
- Fixtures available with 6", 12", 18", 24", 36", and 48" extensions
- Special lens types such as spread lenses and UV lenses can be ordered from WAC and used in place of the supplied clear lens.
- Transformer concealed within the fixture
- 5 year warranty

#### SPECIFICATIONS

Construction:	Die cast Aluminum
Power:	50W, 8W
Input:	120 VAC, 50/60Hz
Dimming:	ELV: 100-10%
Light Source:	Halogen, Retrofit LED
Rated Life:	50000 Hours
Mounting:	Mounts directly to junction box, Can be mounted on ceiling or wall in all orientations
Finish:	Electrostatically Powder Coated:Black, Electrostatically Powder Coated:White
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Damp Location Listed

Fixture Type: \_\_\_\_\_


Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_


Location: \_\_\_\_\_



#### FINISHES:



#### LINE DRAWING:



Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_







Project: \_\_\_\_\_

Location: \_\_\_\_\_

## Low Voltage ME-808

LED MR16 Display Spot Light 3000K

### ACCESSORIES

	<i>Model</i>	<i>Description</i>	<i>Finish</i>
	<b>LENS-16-RED</b> <b>LENS-16-GRN</b> <b>LENS-16-BLU</b> <b>LENS-16-AMB</b>	Colored Lens Colored Lens Colored Lens Colored Lens	Red Green Blue Amber
	<b>LENS-16-FR</b>	Clear/Frosted Lens	Frosted
	<b>LENS-16-SPR</b>	Spread Lens	Spread Lens
	<b>LENS-16-UVF</b>	UV Filter lens	Clear
	<b>LENS-16-BEL</b>	Beam Elongating Lens	Beam Elongating
	<b>LENS-16-HCL</b>	Honeycomb Louver	Black