

Low Voltage ME-808

LED MR16 Display Spot Light 3000K

Model & Wattage	Finish
ME-808 50W	BK Black
ME-808LED 8W	WT White

Example: ME-808-BK

DESCRIPTION

Single Spot Light with electronic transformer. Engineered with an integral transformer and designed for mounting to walls or ceilings, low and line voltage Display Spot Lights deploy optimal accent lighting from surface mounted canopies that can be custom designed with any of WAC low voltage track heads.

FEATURES

- Integral electronic transformer
- Accepts 12V LED MR16, Halogen MR16 lamps up to 50W max
- · LED MR16 included when ordered as LED
- 1 watt minimum load
- Fixtures available with 6", 12", 18", 24", 36", and 48" extensions
- Special lens types such as spread lenses and UV lenses can be ordered from WAC and used in place of the supplied clear lens.
- Transformer concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Die cast Aluminum Construction:

50W, 8W Power:

120 VAC, 50/60Hz Input: ELV: 100-10% Dimming:

Halogen, Retrofit LED **Light Source:**

50000 Hours Rated Life:

Mounts directly to junction box, Can be mounted on Mounting:

ceiling or wall in all orientations

Electrostatically Powder Coated:Black, Electrostatically Finish:

Powder Coated:White

-4°F to 104°F (-20°C to 40°C) **Operating Temp:** UL, cUL, Damp Location Listed Standards:


Fixture Type: Catalog Number: Project: Location:



FINISHES:



LINE DRAWING:





Low Voltage ME-808 LED MR16 Display Spot Light 3000K

Fixture Type:	
Catalog Number:	
Project:	
Location:	

ACCESSORIES				
	Model	Description	Finish	
	LENS-16-RED LENS-16-GRN LENS-16-BLU LENS-16-AMB	Colored Lens Colored Lens Colored Lens Colored Lens	Red Green Blue Amber	
	LENS-16-FR	Clear/Frosted Lens	Frosted	
	LENS-16-SPR	Spread Lens	Spread Lens	
	LENS-16-UVF	UV Filter lens	Clear	
	LENS-16-BEL	Beam Elongating Lens	Beam Elongating	
	LENS-16-HCL	Honeycomb Louver	Black	