

## Low Voltage Multiple Spots

### 1 Light Housing

#### Model & Product

MT-116HS Low Voltage  
Multiple Single Light Non-IC  
Housing

Example: **MT-116HS**

#### DESCRIPTION

Low Voltage Multiple Spots are ideal for perimeter lighting applications in smaller scale retail, commercial and hospitality environments. Square single light gimbal ring style adjustable recessed fixture, available with flanged trim or Invisible Trim™, designed to sit flush with the ceiling for a clean architectural look. Housing, trim, and lamp are sold separately.

#### FEATURES

- Electronic short circuit and overload protection with automatic reset
- Soft start to prolong lamp life
- Transformer concealed within the fixture
- 5 year warranty

#### SPECIFICATIONS

Construction:	Aluminum hardware with mouth blown etched glass diffuser
Input:	120 VAC, 50/60Hz
Dimming:	ELV: 100-10%
Light Source:	Halogen or LED MR16
Mounting:	Supplied with hanger bars, adjustable from 15"-24 1/2" to accommodate various joist construction and grid sizes
Ceiling Thickness:	1/2" - 1"
Standards:	UL, cUL, Damp Location Listed, Non IC

Fixture Type: \_\_\_\_\_



Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_



#### LINE DRAWING:



# WAC LIGHTING

## Low Voltage Multiple Spots

### 1 Light Halogen MR16 Trim

Model	Finish
MT-116	WT/WT White/White
MT-116TL	WT White

Example: **MT-116-WT/WT**

#### DESCRIPTION

Low Voltage Multiple Spots are ideal for perimeter lighting applications in smaller scale retail, commercial and hospitality environments. Square single light gimbal ring style adjustable recessed fixture, available with flanged trim or Invisible Trim™, designed to sit flush with the ceiling for a clean architectural look. Housing, trim, and lamp are sold separately.

#### FEATURES

- Trim version has a 1/4" low profile, Invisible Trim™ sits flush to ceiling
- The supplied clear glass lens can be replaced by a variety of lenses or accessories
- 5 year warranty

#### SPECIFICATIONS

Construction:	Stamped metal trim
Power:	50W
Light Source:	Halogen MR16 ( Sold Separately )
Cut Out:	Trim : 5 3/16" x 5 3/16", Trimless : 5 5/8" x 5 5/8"
Finish:	Electrostatically Powder Coated:White/White, Electrostatically Powder Coated:White
Standards:	UL, cUL, Damp Location Listed

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_




#### FINISHES:



White/White

White

#### LINE DRAWING:



# WAC LIGHTING

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## Low Voltage Multiple Spots

### 1 Light LED MR16 Trim

Model	Finish
MT-116LED	WT/WT White/White
MT-116LEDTL	WT White

Example: **MT-116LED-WT/WT**

#### DESCRIPTION

Low Voltage Multiple Spots are ideal for perimeter lighting applications in smaller scale retail, commercial and hospitality environments. Square single light gimbal ring style adjustable recessed fixture, available with flanged trim or Invisible Trim™, designed to sit flush with the ceiling for a clean architectural look. Housing, trim, and lamp are sold separately.

#### FEATURES

- Trim version has a 1/4" low profile, Invisible Trim™ sits flush to ceiling
- The supplied clear glass lens can be replaced by a variety of lenses or accessories
- 5 year warranty

#### SPECIFICATIONS

Construction:	Stamped metal trim
Power:	7W
Light Source:	LED MR16 ( Included )
Cut Out:	Trim : 5 3/16" x 5 3/16", Trimless : 5 5/8" x 5 5/8"
Finish:	Electrostatically Powder Coated:White/White, Electrostatically Powder Coated:White
Standards:	UL, cUL, Damp Location Listed



#### FINISHES:



White/White

White

#### LINE DRAWING:

