

Low Voltage Multiple Spots

2 Light Housing

Model & Product

MT-216HS Low Voltage Multiple Two Light Non-IC Housing

Example: MT-216HS

DESCRIPTION

Low Voltage Multiple Spots are ideal for perimeter lighting applications in smaller scale retail, commercial and hospitality environments. Square single light gimbal ring style adjustable recessed fixture, available with flanged trim or Invisible Trim[™], designed to sit flush with the ceiling for a clean architectural look. Housing, trim, and lamp are sold separately.

FEATURES

- Electronic short circuit and overload protection with automatic reset
- Soft start to prolong lamp life
- Transformer concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Construction: Aluminum hardware with mouth blown etched glass

diffuser

Input: 120 VAC, 50/60Hz Dimming: ELV: 100-10%

Light Source: Halogen or LED MR16

Mounting: Supplied with hanger bars, adjustable from 15"-24 1/2" to

accommodate various joist construction and grid sizes


Ceiling Thickness: 1/2" - 1"


Standards: UL, cUL, Damp Location Listed, Non IC

Fixture Type:
Catalog Number:
Project:
Location:



LINE DRAWING:







Low Voltage Multiple Spots

2 Light Halogen MR16 Trim

Model Finish

MT-216 WT/WT White/White

MT-216TL WT White

Example: MT-216-WT/WT

DESCRIPTION

Low Voltage Multiple Spots are ideal for perimeter lighting applications in smaller scale retail, commercial and hospitality environments. Square single light gimbal ring style adjustable recessed fixture, available with flanged trim or Invisible Trim[™], designed to sit flush with the ceiling for a clean architectural look. Housing, trim, and lamp are sold separately.

FEATURES

- Trim version has a 1/4" low profile, Invisible Trim™ sits flush to ceiling
- The supplied clear glass lens can be replaced by a variety of lenses or accessories
- 5 year warranty

SPECIFICATIONS

Construction: Stamped metal trim

Power: 100W

Light Source: Halogen MR16 (Sold Separately)

Cut Out: Trim: 5 3/16" x 9 1/8", Trimless: 5 5/8" x 9 5/8"

Finish: Electrostatically Powder Coated: White/White,

Electrostatically Powder Coated: White

Lill Barry Lasting Listed

Standards: UL, cUL, Damp Location Listed





FINISHES:



е

LINE DRAWING:







Low Voltage Multiple Spots

2 Light LED MR16 Trim

Model	Finish
MT-216LED	WT/WT White/White
MT-216LEDTL	WT White

Example: MT-216LED-WT/WT

DESCRIPTION

Low Voltage Multiple Spots are ideal for perimeter lighting applications in smaller scale retail, commercial and hospitality environments. Square single light gimbal ring style adjustable recessed fixture, available with flanged trim or Invisible Trim™, designed to sit flush with the ceiling for a clean architectural look. Housing, trim, and lamp are sold separately.

FEATURES

- Trim version has a 1/4" low profile, Invisible Trim™ sits flush to ceiling
- The supplied clear glass lens can be replaced by a variety of lenses or accessories
- 5 year warranty

SPECIFICATIONS

Construction: Stamped metal trim

Power: 14W

Light Source: LED MR16 (Included)

Cut Out: Trim: 5 3/16" x 9 1/8", Trimless: 5 5/8" x 9 5/8"

Finish: Electrostatically Powder Coated: White/White,

Electrostatically Powder Coated: White

Standards: UL, cUL, Damp Location Listed

Fixture Type:

Catalog Number:

Project:

Location:



FINISHES:



LINE DRAWING:

