

INSTALLATION INSTRUCTIONS FOR 4134

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER .
AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

READ AND SAVE THESE INSTRUCTIONS

ASSEMBLING THE FIXTURE (Fig. 1)

1. Shut off the power at the fuse box or circuit breaker box. If necessary, remove the old fixture including the mounting hardware.
2. Carefully remove the new fixture from the carton and check that all parts are included as shown in the illustration.
3. Thread the rod (F) onto the nipple (G).

MOUNTING THE FIXTURE (Fig.1)

4. Thread the two mounting screws (A) (Size: #8-32*1.2"L) part way into the crossbar (B). Secure crossbar (B) to the junction box (not provided) with junction box screws (C) (Size: #8-32*0.6"L). The length of mounting screws (A) into crossbar (B) may be adjusted if necessary. The side of the cross bar marked "GND" must face out.

CONNECTING THE WIRES (Fig.2)

5. At this point, connect the electrical wires as shown in Fig. 2, making sure that all wire connectors are secured. If your outlet box has a ground wire (green or bare copper), connect the fixture's ground wire to it. Otherwise, connect the fixture's ground wire directly to the mounting plate using the green screw provided. After the wires are connected, tuck them carefully inside the outlet box.

COMPLETING THE INSTALLATION (Fig. 1)

6. Align canopy (D) onto mounting screws (A) and secure with finials (E).
7. Install the light bulbs (Included) in accordance with the fixture's specifications. **(DO NOT EXCEED THE MAXIMUM WATTAGE!) (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)**

Your installation is now complete. Return power to the outlet box and test the fixture.

