

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## Ocularc 2.0

### Open Reflector Square

Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
R2BSD	F 45°	927 2700K - 90	650	1235	BK Black
		930 3000K - 90	695	1322	BN Brushed Nickel
	N 25°	927 2700K - 90	655	2301	HZWT Haze/White
		930 3000K - 90	700	2462	WT White

Example: **R2BSD-F927-BK**

#### DESCRIPTION

Engineered with state of the art LED and driver technology, Ocularc 3.0, 3.0, 1.0 family of recessed lighting offers various styles, IC and Airtight Rated New Construction and Remodel, and low glare optical distributions to beautifully illuminate a diverse range of applications.

#### FEATURES

- Cutout 3 1/16"
- Single spot light source
- Ceiling thickness: 1/2" - 1"
- Sold as New Construction, may be reconfigured in the field for Remodel
- Driver concealed within the fixture
- 5 year warranty

#### SPECIFICATIONS

<b>Construction:</b>	Die-cast aluminum trim with aluminum heat sink
<b>Power:</b>	9W
<b>Input:</b>	120 VAC, 50/60Hz
<b>Dimming:</b>	ELV: 100-5% , 0-10V: 100-5%, TRIAC: 100-5%
<b>Light Source:</b>	Integrated LED 3 Step Mac Adam Ellipse
<b>Rated Life:</b>	50000 Hours
<b>Cut Out:</b>	3 1/16"
<b>Finish:</b>	Electrostatically Powder Coated: Black, Brushed Nickel, Haze/White, White
<b>Ceiling Thickness:</b>	1/2" - 1"
<b>Operating Temp:</b>	-4°F to 104°F (-20°C to 40°C)
<b>Standards:</b>	ETL, cETL, Wet Location Listed, Energy Star 2.0, Title 24 JA8-2019 Compliant, IC, Airtight



#### FINISHES:



#### LINE DRAWING:

