

# OCULARC 3.5

## Adjustable Pinhole - R3CRPT, R3CRPL

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_

### PRODUCT DESCRIPTION

Ocularc 3.5 offers performance features in a simple but versatile package for residential and commercial applications alike. One housing can be used for downlight, adjustable, pinhole, wall wash trims.

### FEATURES

- 3 beam angle options included:  
Narrow flood beam film pre-installed, interchangeable flood beam film supplied, remove film for spot beam.
- IC-Rated, Airtight, New Construction
- Adjustable LED light engine included with housing:  
Vertical Adjustment 0-30°, Horizontal Adjustment 365°
- Shallow housing under 4" depth
- 5 year warranty

### SPECIFICATIONS

- Construction:** Die-cast aluminum trim and heat sink
- Dimming:** 100% - 1% TRIAC, ELV  
100% - 5%, 0-10V
- Input Power:** 13.5W, 120V-277V 50/60Hz
- Light Source:** High output COB LED rated life of 50,000 hours.
- Mounting:** Retention clips firmly hold trim to housing. Cutout 4¼"
- Finish:** Powder coated white.
- Ceiling thickness:** ½" - 1"
- Standards:** UL & cUL, Wet location listed. Energy Star® 2.0  
Title 24 JA8-2016 Compliant
- Operating Temperature:** -4°F to 104°F (-20°C to 40°C)

Trims (Order Housing Separately)	Model	Beam	Color Temp	Lumens	CBCP	Finish
<p><b>R3CRPT</b> Round Trim Adjustable Pinhole</p>	Spot 16°	927 2700K	720 5008	<b>WT</b> White <b>BK</b> Black		
		930 3000K	770 5385			
		935 3500K	790 5493			
	Narrow Flood 32°	940 4000K	825 5762			
		927 2700K	630 1425			
		930 3000K	675 1532			
	Flood 44°	935 3500K	690 1563			
		940 4000K	720 1640			
		927 2700K	580 824			
<p><b>R3CRPL</b> Round Trimless Adjustable Pinhole</p>	Spot 16°	930 3000K	770 5385			
		935 3500K	790 5493			
		940 4000K	825 5762			
	Narrow Flood 32°	927 2700K	630 1425			
		930 3000K	675 1532			
		935 3500K	690 1563			
	Flood 44°	940 4000K	720 1640			
		927 2700K	580 824			
		930 3000K	625 886			
		935 3500K	635 904			
		940 4000K	665 948			

R3CRP\_\_-\_\_\_\_\_

Example: R3CRPT-WT

wacighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760

# OCULARC 3.5

## Adjustable Pinhole - R3CRPT, R3CRPL

Housing (Required) - Order separately from trims

	Model	Power	Color Temp
	<b>R3CRN-11</b> IC-Rated Airtight	13.5W	<b>927</b> 2700K <b>930</b> 3000K <b>935</b> 3500K <b>940</b> 4000K
	<b>R3CRR-11</b> Non IC Airtight	13.5W	<b>927</b> 2700K <b>930</b> 3000K
	<b>R3CRR-11</b> Non IC Airtight	13.5W	<b>935</b> 3500K <b>940</b> 4000K

**R3CR\_\_-11-\_\_**  
Example: **R3CRN-11-927**

### FEATURES

- Adjustable LED light engine included with housing:  
Vertical Adjustment 0-30°, Horizontal Adjustment 365°
- Trim or trimless with die-cast spackle frame included.
- Accepts one optional honeycomb louver or optical lens.

**GLARE CONTROL ACCESSORIES** sold separately

<b>LENS-16</b>	<b>HCL</b>	Honeycomb Louver
----------------	------------	------------------

**LENS ACCESSORIES** sold separately

<b>LENS-16</b>	<b>AMB</b>	Amber
	<b>RED</b>	Red
	<b>FR</b>	Frosted
	<b>SPR</b>	Spread
	<b>BEL</b>	Beam Elongating

**wacighting.com**  
Phone (800) 526.2588  
Fax (800) 526.2585

**Headquarters/Eastern Distribution Center**  
44 Harbor Park Drive  
Port Washington, NY 11050

**Central Distribution Center**  
1600 Distribution Ct  
Lithia Springs, GA 30122

**Western Distribution Center**  
1750 Archibald Avenue  
Ontario, CA 91760