

# OCULARC 3.5

Wall Wash - R3CRWT, R3CRWL

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

## PRODUCT DESCRIPTION

Ocularc 3.5 offers performance features in a simple but versatile package for residential and commercial applications alike. One housing can be used for downlight, adjustable, pinhole, wall wash trims.

## FEATURES

- 3 beam angle options included: For Wall Wash trim optimal optics is light engine with no film installed.
- IC-Rated, Airtight, New Construction
- Adjustable LED light engine included with housing
- Shallow housing under 4" depth
- 5 year warranty

## SPECIFICATIONS

**Construction:** Die-cast aluminum trim and heat sink

**Dimming:** 100% - 1% TRIAC, ELV  
100% - 5%, 0-10V

**Input Power:** 13.5W, 120V-277V 50/60Hz

**Light Source:** High output COB LED rated life of 50,000 hours.

**Mounting:** Retention clips firmly hold trim to housing. Cutout 4¼"

**Finish:** Powder coated white, enamel-coated haze.

**Ceiling thickness:** ½" - 1"

**Standards:** UL & cUL, Wet location listed. Title 24 JA8-2016 Compliant

**Operating Temperature:** -4°F to 104°F (-20°C to 40°C)

Trims (Order Housing Separately)	Model	Beam	Color Temp	Lumens	CBCP	Finish
	<b>R3CRWT</b> <i>Round Trim</i> <i>Wall Wash</i>	Asymmetrical	927 2700K 930 3000K 935 3500K 940 4000K	590 635 650 680	N/A	<b>HZWT</b> Haze/White <b>WT</b> White <b>BK</b> Black
	<b>R3CRWL</b> <i>Round Trimless</i> <i>Wall Wash</i>	Asymmetrical	927 2700K 930 3000K 935 3500K 940 4000K	590 635 650 680	N/A	<b>HZ</b> Haze <b>WT</b> White <b>BK</b> Black

## R3CRW\_\_ -

Example: R3CRWT-WT

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive

Port Washington, NY 11050

Central Distribution Center

1600 Distribution Ct

Lithia Springs, GA 30122

Western Distribution Center

1750 Archibald Avenue

Ontario, CA 91760

# OCULARC 3.5

## Wall Wash - R3CRWT, R3CRWL

# WAC LIGHTING

Responsible Lighting®

Housing (Required) - Order separately from trims	Model	Power	Color Temp
	<b>R3CRN-11</b> IC-Rated Airtight	13.5W	<b>927</b> 2700K <b>930</b> 3000K <b>935</b> 3500K <b>940</b> 4000K
<p>Remodel Trim</p>	<b>R3CRR-11</b> Non IC Airtight	13.5W	<b>927</b> 2700K <b>930</b> 3000K
<p>Remodel Trimless</p>	<b>R3CRRL-11</b> Non IC Airtight	13.5W	<b>935</b> 3500K <b>940</b> 4000K

### R3CR\_\_-11-\_\_

Example: R3CRN-11-927

#### FEATURES

- Adjustable LED light engine included with housing:  
Optimal Vertical Adjustment for Wall Wash is 15° indexed position
- Trim or trimless with die-cast spackle frame included.
- Accepts one optional honeycomb louver or optical lens.

#### GLARE CONTROL ACCESSORIES sold separately

<b>LENS-16</b>	<b>HCL</b>	Honeycomb Louver
----------------	------------	------------------

#### LENS ACCESSORIES sold separately

<b>LENS-16</b>	<b>AMB</b>	Amber
	<b>RED</b>	Red
	<b>FR</b>	Frosted
	<b>SPR</b>	Spread
	<b>BEL</b>	Beam Elongating

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive

Port Washington, NY 11050

Central Distribution Center

1600 Distribution Ct

Lithia Springs, GA 30122

Western Distribution Center

1750 Archibald Avenue

Ontario, CA 91760