

**CALYPSO Outdoor**  
**3-730-xx**

oxygen

FIXTURE TYPE \_\_\_\_\_

LOCATION \_\_\_\_\_

PROJECT \_\_\_\_\_

DATE \_\_\_\_\_



-22 Oiled Bronze



-16 Gray

**LIGHT SOURCE** 1 x 12.1W LED, 3000K, CRI 90

**LUMINAIRE POWER** 14.4W at 120V

**RATED LIFE** 60000 hr RL

**OPTIONAL COLOR TEMPERATURES** 2700K, 3500K, 4000K

**LUMEN OUTPUT** Delivered: 531 lm (LM-79)

**INPUT VOLTAGE** 120V to 277V, 50/60Hz

**DRIVER OUTPUT** 350mA, 14.7W max power

**DIMMING** TRIAC and ELV dimming at 120V AC; 0-10V dimming, 100% to 1% current output



**CONSTRUCTION** Cast Aluminum and Polycarbonate

**DIFFUSER** - White Polycarbonate

**FINISHES** Gray (-16), Oiled Bronze (-22)

**MOUNTING** 4" Octagonal J-Box\*,  
4" Square J-Box\* with a single device mud ring\*\*  
\*Deep J-Box (Required to house driver)  
\*\*Mud ring must be mounted horizontally  
(Installer must provide a bead of caulk between fixture housing and mounting surface)

**STANDARDS** UL Wet listed, ADA Compliant, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



**DIMENSIONS**

**W:** 4.25"  
**H:** 16.50"  
**Ext:** 2.25"  
**M.C:** 8.00" From top of fixture

Order example for standard fixture:  
**3-730-22** (x- Voltage - xxx-Sequence # - xx-Finish)  
3: 120V to 277V  
Order example for optional color temperatures: **3-730-2722**  
27: 2700K, 35: 3500K, 40: 4000K

