

ELITE Ceiling Mount
3-645-xx

oxygen

FIXTURE TYPE _____

LOCATION _____

PROJECT _____

DATE _____



-6 White



-15 Black



-22 Oiled Bronze



-24 Satin Nickel

LIGHT SOURCE 1 x 13W LED with Driver on board, 3000K, CRI 90

LUMINAIRE POWER 14W at 120V

RATED LIFE 50000 hr RL

OPTIONAL COLOR TEMPERATURES 3000K Only

LUMEN OUTPUT Delivered: 823 lm (LM-79)

INPUT VOLTAGE 120V AC, 50/60Hz

DRIVER OUTPUT N/A

DIMMING TRIAC Dimming



CONSTRUCTION Cast Aluminum Housing

DIFFUSER - Etched White Glass

FINISHES White (-6), Black (-15),
Oiled Bronze (-22), Satin Nickel (-24)

MOUNTING 4" Octagonal J-Box

STANDARDS ETL Wet listed, Conforms to UL STD 1598,
Certified CAN/CSA STD C22.2 No 250.0.



DIMENSIONS

Dia: 7.00"

H: 1.00"

Note: For wet locations, installer must provide a bead of caulk between fixture housing and mounting surface.

Order example for standard fixture:

3-645-15 (x- Voltage - xxx-Sequence # - xx-Finish)

3: 120V Only

