

HALO Wall Sconce
3-535-xx



FIXTURE TYPE _____

LOCATION _____

PROJECT _____

DATE _____



-25 Satin Copper



-14 Polished Chrome




-24 Satin Nickel



-40 Aged Brass

- LIGHT SOURCE** 1 x 10.1W LED, 3000K, CRI 90
- LUMINAIRE POWER** 12.3W at 120V
- RATED LIFE** 60000 hr RL
- OPTIONAL COLOR TEMPERATURES** 2700K, 3500K, 4000K
- LUMEN OUTPUT** Delivered: 709 lm (LM-79)
- INPUT VOLTAGE** 120V to 277V AC, 50/60Hz
- DRIVER OUTPUT** 350mA, 14.7W max power
- DIMMING** TRIAC and ELV dimming at 120V AC; 0-10V dimming, 100% to 1% current output
- CONSTRUCTION** Plated Steel and Acrylic
- DIFFUSER** - Matte White Acrylic
- FINISHES** Polished Chrome (-14), Satin Nickel (-24), Satin Copper (-25), Aged Brass (-40)
- MOUNTING** 2" x 3" J-Box*, 4" Octagonal J-Box, 4" Square J-Box with a single device mud ring*
* Must be mounted horizontally
- STANDARDS** UL Dry/Damp listed, ADA Compliant, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.
- NOTE** Backplate is required



DIMENSIONS

- W:** 5.50"
- H:** 14.25"
- Ext:** 3.25"
- M.C:** 11.50" From top of fixture

Order example for standard fixture:
3-535-24 (x- Voltage - xxx-Sequence # - xx-Finish)
 3: 120V to 277V
 Order example for optional color temperatures: **3-535-2724**
 27: 2700K, 35: 3500K, 40: 4000K

