

# MIRO Chandelier

## 3-605-xx

oxygen

FIXTURE TYPE \_\_\_\_\_

LOCATION \_\_\_\_\_

PROJECT \_\_\_\_\_

DATE \_\_\_\_\_




-24 Satin Nickel



-40 Aged Brass

<b>LIGHT SOURCE</b>	LED Array, 3000K, CRI 90
<b>LUMINAIRE POWER</b>	94W at 120V
<b>RATED LIFE</b>	50000 hr RL
<b>OPTIONAL COLOR TEMPERATURES</b>	3000K
<b>LUMEN OUTPUT</b>	Delivered: 2428 lm (LM-79)
<b>INPUT VOLTAGE</b>	120V AC, 60Hz
<b>DRIVER OUTPUT</b>	720mA, 30.24W max power per driver (3 drivers total - 90.72W total max output)
<b>DIMMING</b>	TRIAC Dimming
<b>CONSTRUCTION</b>	Cold Rolled Steel Housing and Canopy
<b>DIFFUSER</b>	- Clear Bubble Acrylic
<b>FINISHES</b>	Satin Nickel (-24), Aged Brass (-40)
<b>MOUNTING</b>	4" Octagonal J-Box
<b>STANDARDS</b>	ETL Damp listed, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



### DIMENSIONS

**Dia. Canopy:** 7.875"

**W. Fixture:** 26.00"

**H. Fixture:** 28.50"

**Supplied with 2-8", 2-12", and 3-16"**  
**stems to customize hanging height**

Note: Canopy swivel allows up to a 22° slope

Order example for standard fixture:

**3-605-24** (x- Voltage - xxx-Sequence # - xx-Finish)

**3:** 120V Only

