Oslo Ceiling Fan 3-101-xx



		LOCATION		
PROJECT		DATE		
		-6 White With optional light kit Control of the optional light kit	Join a stateJoin a state <th>-20 Polished Nickel -20 Polished Nickel With optional light kit -40 Aged Brass</th>	-20 Polished Nickel -20 Polished Nickel With optional light kit -40 Aged Brass
24 Satin Nickel wit	h Optional LED Light kit	With optional light kit	With optional light kit	With optional light k
	h Optional LED Light kit 4 ABS Blades / 52" Blade Swee 153x18 Motor 4" and 6" downrod (Included) Optional downrods available fo 3 Speeds - Reversible 0.54A on high / 0.28A on low 64W on high / 16W on low 147 rpm on high / 72 rpm on lo Wall Control (Included) Remote Control 3-8-1000-0 (O	ep / 14° Blade-Pitch r high ceilings w	With optional light kit	With optional light k
SPECIFICATIONS	4 ABS Blades / 52" Blade Sweet 153x18 Motor 4" and 6" downrod (Included) Optional downrods available fo 3 Speeds - Reversible 0.54A on high / 0.28A on low 64W on high / 16W on low 147 rpm on high / 72 rpm on lo Wall Control (Included)	ep / 14° Blade-Pitch r high ceilings w	With optional light kit	
SPECIFICATIONS NPUT VOLTAGE ENERGY	4 ABS Blades / 52" Blade Sweet 153x18 Motor 4" and 6" downrod (Included) Optional downrods available fo 3 Speeds - Reversible 0.54A on high / 0.28A on low 64W on high / 16W on low 147 rpm on high / 72 rpm on lo Wall Control (Included) Remote Control 3-8-1000-0 (O	ep / 14° Blade-Pitch r high ceilings w ptional - Not Included)		
24 Satin Nickel wit SPECIFICATIONS INPUT VOLTAGE ENERGY SPECIFICATIONS FINISHES	4 ABS Blades / 52" Blade Swea 153x18 Motor 4" and 6" downrod (Included) Optional downrods available fo 3 Speeds - Reversible 0.54A on high / 0.28A on low 64W on high / 16W on low 147 rpm on high / 72 rpm on lo Wall Control (Included) Remote Control 3-8-1000-0 (O 120V - AC Motor Airflow: 4991 CFM Electric Energy Consuption: 64 V Airflow efficiency: 78 CFM/W	ep / 14° Blade-Pitch r high ceilings w ptional - Not Included) W (Excludes Light) Nickel (-20)*,		52.00" 14.50"
SPECIFICATIONS INPUT VOLTAGE ENERGY SPECIFICATIONS	4 ABS Blades / 52" Blade Swee 153x18 Motor 4" and 6" downrod (Included) Optional downrods available fo 3 Speeds - Reversible 0.54A on high / 0.28A on low 64W on high / 16W on low 147 rpm on high / 72 rpm on lo Wall Control (Included) Remote Control 3-8-1000-0 (O 120V - AC Motor Airflow: 4991 CFM Electric Energy Consuption: 64 N Airflow efficiency: 78 CFM/W Note: Measured at high speed White (-6), Black (-15), Polished	ep / 14° Blade-Pitch r high ceilings w ptional - Not Included) W (Excludes Light) Nickel (-20)*, I (-24), Aged Brass (-40)	DIMENSIONS Blade Sweep: Ht.: Ceiling to Blade: Note: Measured	Blade Sweep 52.00" 14.50"

LIGHT KIT NUMBER	3-9-101	UL damp	\$12	3,770 Cubic Feet Per Minute
LUMEN OUTPUT	Delivered: 429 lm (LM-79)		\$3 I I \$34 Cost Range of Similar Models (19" – 84")	The higher the airflow, the more air the fan will move Airflow Efficiency: 88 Cubic Feet Per Minute Per Watt
LIGHT SOURCE	LED Light kit 18W, 3000K, 90CRI Dimmable LED with Matte White Glass diffuser		Based on 12 cents per kWh and 6.4 hours use per day Your cost depends on rates and use Energy Use: 43 Watts All estimates based on typical use, excluding lights	ftc.gov/energy