

ZENITH Wall Sconce

3-556-xx

oxygen

FIXTURE TYPE _____

LOCATION _____

PROJECT _____

DATE _____




-24 Satin Nickel



-14 Polished Chrome





-22 Oiled Bronze



-40 Aged Brass

LIGHT SOURCE	1 x 12.2W LED, 3000K, CRI 90
LUMINAIRE POWER	14.6W at 120V
RATED LIFE	60000 hr RL
OPTIONAL COLOR TEMPERATURES	2700K, 3500K, 4000K
LUMEN OUTPUT	Delivered: 942 lm (LM-79)
INPUT VOLTAGE	120V to 277V AC, 50/60Hz
DRIVER OUTPUT	350mA, 14.7W max
DIMMING	TRIAC and ELV dimming at 120V AC; 0-10V dimming, 100% to 10% current output
CONSTRUCTION	Plated Steel and Acrylic
DIFFUSER	Matte White Acrylic
FINISHES	Polished Chrome (-14), Oiled Bronze (-22), Satin Nickel (-24), Aged Brass (-40)
MOUNTING	4" Octagonal J-Box* with optional backplate 4"x4" Square J-Box* with single device mud ring * Deep J-Box (Required to house driver)
STANDARDS	ETL Dry/Damp listed, ADA Compliant, Conforms to UL STD 1598, Certified CAN/CSA, STD C22.2 No 250.0.



DIMENSIONS

W: 3.50"

H: 15.125"

Ext: 3.50"

M.C: 13.00" From Top of Fixture

Order example for standard fixture:

3-556-xx (x-Voltage - xxx-Sequence # - xx-Finish)

Order example for optional color temperatures: **3-556-2724**

27: 2700K, **35:** 3500K, **40:** 4000K

