

FM-4514-35

Project:

Location:

Fixture Type:

Catalog Number:

## **AVAILABLE FINISHES:**



# Puck

FM-4514

#### PRODUCT DESCRIPTION

Celebrate style and performance with this curvaceous LED luminaire featuring a blow molded diffuser to deliver ample lighting with smooth and continuous ELV dimming capabilities. Thechrome ring integrates LED arrays for a uniform deliverance without shadows commonly found in conventional flush mounts. Use as wall or ceiling mount with unbridled creativity.

## **FEATURES**

- Driver concealed within the fixture
- Twist-lock installation
- Secondary lens to spread light evenly

#### **SPECIFICATIONS**

Rated Life	59000 Hours
Standards	ETL, cETL,Damp Location Listed,Title 24 JA8: 2019 Compliant,Energ
	Star 2.0

Input 120-277V,50/60Hz Dimming ELV: 100-10%,TRIAC: 100-5%

Mounting Can be mounted on ceiling or wall in all orientations

**Color Temp** 3500K CRI 90

Construction Aluminum hardware, acrylic diffuser

#### REPLACEMENT PARTS


RPL-SHA-4514 - Shade

Model & Size	Color Temp	Finish	<b>LED Watts</b>	LED Lumens	<b>Delivered Lumens</b>
FM-4514 14"	3500K	BN Brushed Nickel	20W	1500	1464

Example: FM-4514-35-BN

For custom requests please contact customs@modernforms.com





FM-4516-35

# Project:

Location:

Fixture Type:

Catalog Number:

## **AVAILABLE FINISHES:**



# **Puck**

FM-4516

#### PRODUCT DESCRIPTION

Celebrate style and performance with this curvaceous LED luminaire featuring a blow molded diffuser to deliver ample lighting with smooth and continuous ELV dimming capabilities. Thechrome ring integrates LED arrays for a uniform deliverance without shadows commonly found in conventional flush mounts. Use as wall or ceiling mount with unbridled creativity.

## **FEATURES**

- Driver concealed within the fixture
- Twist-lock installation
- Secondary lens to spread light evenly

## **SPECIFICATIONS**

Rated Life	59000 Hours

Standards ETL, cETL,Damp Location Listed,Title 24 JA8: 2019 Compliant,Energy

Star 2.0

**Input** 120-277V,50/60Hz

**Dimming** ELV: 100-10%,TRIAC: 100-5%

**Mounting** Can be mounted on ceiling or wall in all orientations

Color Temp 3500K CRI 90

Construction Aluminum hardware, acrylic diffuser

#### REPLACEMENT PARTS

RPL-SHA-4516 - Shade

Model & Siz	ze	Color Temp	Finish		LED Watts	LED Lumens	<b>Delivered Lumens</b>
FM-4516	16"	3500K	BN	Brushed Nickel	27W	2300	2152

Example: FM-4516-35-BN

For custom requests please contact customs@modernforms.com