

INSTALLATION INSTRUCTIONS FOR P5042

For Wall Mount Fixture

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER .
AVERTISSEMENT ! COUPER LE COURANT AUNIVEAU DE FUSIBLES OU DU DISJONCTEUR

PREPARATION

1. Shut off the power at the circuit breaker box (avertissement! couper le courant au niveau des fusibles ou du disjoncteur) and remove the old fixture, including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take not to loose any small parts necessary for installation.

MOUNTING THE FIXTURE (FIG. 1)

3. The circular strap (part#A-021R-110) contains several pairs of threaded holes. Find the pair of holes that match the hole spacing in your fixture canopy and thread the two mounting screws(Size:8-32*1/2"L) part way into the circular strap. Secure the circular strap to the outlet box (not provided) with mounting screws through slotted holes in circular strap.

4. CONNECTING THE WIRES (FIG. 2)

5. At this point, connect the electrical wire as shown in Fig. 2, making sure that all wire connectors are secured. If your outlet has a ground wire (green or bare copper), connect the fixtures ground wire to it. Otherwise, connect the fixture ground wire directly to the circular strap using the green screw provided. After wires are connected, tuck them carefully inside the junction box.

6. Install the proper light bulbs(2-60W TYPE T10) for your fixture,
DO NOT EXCEED THE SPECIFIED WATTAGE!
(NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE)
7. Place the glass over the socket and secure by turning clockwise.

Return the power to the junction box and test the fixture. Your installation is now complete.

IMPORTANT: Fixture should be installed by a qualified electrician to ensure proper wiring and installation.

