



MT-4 - 1 Light, 2 Light, 3 Light, 4 Light Silo Multiples - Trimless

WAC LIGHTING Responsible Lighting®



Adjustable between 15° - 45°

Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Retractable, adjustable spot lights

FEATURES

- Continuously adjustable beam angle between 15° and 45°
- 365° horizontal rotation and 180° vertical aiming
- Independently adjustable and retractable heads
- Accommodates one lens and glare control accessory
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Die-cast aluminum head with rotatable front face. Steel housing and trim.

Light Source: High output LED. Rated life of 50,000 hours

Input: Universal 120V - 277V AC 50/60 Hz.

Dimming: Electronic low voltage (ELV), TRIAC, 0-10V

Mounting: Accommodates 1/2" - 1" ceiling thickness.

Finish: Electrostatically powder coated Black and White

Standards: UL & cUL Damp Location listed, Title 24 JA8-2016 Compliant, Airtight

Model	Heads	Power	Color Temp	Beam	Lumens *Ref. Output	CBCP *Ref. Output	Finish (Trim/Interior)			
MT-4	1		10L 10W IC	927 2700K 90	15°	745	3460			
			15L 14W Non IC	930 3000K 90						
				935 3500K 90				45°	1130	1870
				940 4000K 90						
MT-4	2		10L 20W IC	927 2700K 90	15°	745 x2	3460 x2			
			15L 28W Non IC	930 3000K 90						
				935 3500K 90				45°	1130 x2	1870 x2
				940 4000K 90						
MT-4	3		10L 30W IC	927 2700K 90	15°	745 x3	3460 x3			
			15L 42W Non IC	930 3000K 90						
				935 3500K 90				45°	1130 x3	1870 x3
				940 4000K 90						
MT-4	4		10L 40W IC	927 2700K 90	15°	745 x4	3460 x4			
			15L 56W Non IC	930 3000K 90						
				935 3500K 90				45°	1130 x4	1870 x4
				940 4000K 90						

MT-4 _____ L- _____ - _____

Example: MT-4215L-930-WTWT

*Reference output is 930(CRI 90 3000k) at 15(14W). Reference photometric performance on next page for other combinations.

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

MT-4 - 1 Light, 2 Light, 3 Light, 4 Light Silo Multiples - Trimless

WAC LIGHTING

Responsible Lighting®

PHOTOMETRIC PERFORMANCE (PER HEAD):

10W

Model	Power	Color Temp	CRI	Beam	Lumens	CBCP
MT-4110	10W	927 2700K	90	15°	520	2440
				45°	780	1305
		930 3000K	90	15°	555	2585
				45°	835	1400
		935 3500K	90	15°	560	2580
				45°	850	1405
	940 4000K	90	15°	580	2695	
			45°	875	1450	

14W

Model	Power	Color Temp	CRI	Beam	Lumens	CBCP
MT-4115	14W	927 2700K	90	15°	690	3250
				45°	1050	1735
		930 3000K	90	15°	745	3460
				45°	1130	1870
		935 3500K	90	15°	750	3425
				45°	1140	1870
	940 4000K	90	15°	780	3605	
			45°	1185	1965	

ACCOMMODATES ONE LENS ACCESSORY AND ONE GLARE CONTROL ACCESSORY

FLAT LENS

Amber	LENS-16-AMB
Blue	LENS-16-BLU
Green	LENS-16-GRN
Red	LENS-16-RED

FLAT LENS

Frosted	LENS-16-FR
Spread	LENS-16-SPR
Beam Elongating	LENS-16-BEL

GLARE CONTROL

Cross louver - Black	LENS-16P-CRL-BK
Cross louver - White	LENS-16P-CRL-WT
Snoot - Black	LENS-16-SNOOT-BK
Snoot - White	LENS-16-SNOOT-WT
Honey Comb Louver	LENS-16-HCL

REPLACEMENT HEADS (INCLUDES: ONE HEAD, LED, AND DRIVER)

Model	Power	
4MT-410-927-BK		
4MT-410-930-BK	10W	IC
4MT-410-935-BK		
4MT-410-940-BK		
4MT-410-927-WT		
4MT-410-930-WT	10W	IC
4MT-410-935-WT		
4MT-410-940-WT		
4MT-415-927-BK		
4MT-415-930-BK	14W	Non IC
4MT-415-935-BK		
4MT-415-940-BK		
4MT-415-927-WT		
4MT-415-930-WT	14W	Non IC
4MT-415-935-WT		
4MT-415-940-WT		

Example: **4MT-410-930-WT**

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760