

FLOS

■ FU136730 Black

Smithfield Suspension Pro

Designed by Jasper Morrison, 2009



30W - 2791lm - 2700K - CRI> 95

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

EAN	8059607010655
Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
LED type	LED Module
Power (W)	30
System power (W)	30
System flux (lm)	2791

Physical

Color	Black
Cord length (in)	106
Canopy dimension (mm)	36
Net weight (lb)	12.79
Package volume (in)	9536.17
IP internal	20




Download


[Mounting instructions](#)



Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional



Photometric

Lighting type	Direct
Light distribution	Roto symmetric
CCT (K)	2700
CRI>	95

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	120
LED voltage Vf (Vdc)	null
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmable 0-10V
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

Spare Parts



- | | | |
|-----|---|-----------|
| 01. | Black ceiling rose assembly | RAU369230 |
| 02. | Kit of 5 or rings | RF05382 |
| 03. | Power Cord for Smithfield | RF19342 |
| 04. | 3 mt steel cable ø1,2 with 19
winded wires | RF29665 |
| 04. | 4mt steel wire Ø1,2 with 19
winded wires | RF01089 |
| 06. | Methacrylate diffuser | RF19022 |



RAU369230

Black ceiling rose assembly



RF05382

Kit of 5 or rings



RF19342

Power Cord for Smithfield

FLOS

RF29665

3 mt steel cable \varnothing 1,2 with 19
winded wires



RF01089

4mt steel wire \varnothing 1,2 with 19
winded wires



RF19022

Methacrylate diffuser