

# KILTER II

6W | 375 lm | 2700K

T30-640-6W-2700K-S14D-FR-120V

Kilter bulb 640mm length 6W 2700K S14D frosted 120V

tala®

The Kilter bulb by Tala is a new take on an architectural lighting staple. Defined by its tubular shape, Kilter achieves consistent light throw and reduce shadowed endpoints while offering Tala's signature dimming characteristics.



## PHYSICAL

Bulb diameter:	1 1/8in
Bulb length:	25 2/8in
Glass shape:	T30
Base:	S14D
Materials:	Glass & nickel
Glass finish:	Frosted
Weight:	195g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54

## ELECTRICAL

Power:	6W
Current:	0.06A
Voltage:	110-120V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	63 lm/W
Lifetime:	15,000 hrs

## ILLUMINATION

CCT:	2700K
Lumens:	375 lm
Incandescent equiv.:	32W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	75
TM30 - Rg	97
TM30 - Rf	94

IES/LDT photometry files and product photography available on request



## DIMMING

Dimmable 0-100%  
Recommended dimmer: Lutron Diva DVELV-300P  
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,  
London, E2 9DG, United Kingdom

Tala North America, Inc., 2 Research Place,  
Suite 300, Rockville, MD 20850

us.tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

## LOGISTICAL

Unit Packaging	Outer Carton
PC/Ctn: 1	PC/Ctn: 4
Gross weight: 600 g	Gross weight: 1.9 kg
L 27 4/8 x W 2 6/8 x H 2 6/8 in	L 27 6/8 x W 11 3/8 x H 3 in

## WARRANTY

2 years

## EAN

5060915712158

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights

# KILTER WALL LIGHT

tala®

SKU: KLT-WL-DG-01-US

FINISH: DARK GREY

The Kilter Wall Light by Tala mounts flush to the wall or ceiling to create a seamless exchange with the environment. The circular aluminium shell is designed to house Tala's Kilter S14d light sources. IP44 rated for outdoor use.



## PHYSICAL

Spouce:	L 2 1/8 x W 4 2/8 x H 4 2/8in
Not used:	L - x W - x H -in
Cable length:	-
Materials:	Powder coated aluminium
Finish:	Dark Grey
Weight:	480g
IP rating:	IP44
Base:	S14D

## ELECTRICAL

Appliance class	Class I
Power:	6W MAX
Voltage:	110-120V~
Frequency:	50/60Hz



## DIMMING

Recommended dimmer: Lutron Diva DVELV-300P  
Included Dimmer: N/A  
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,  
London, E2 9DG, United Kingdom

## LOGISTICAL

Unit Packaging  
PC/Ctn: 1  
Gross weight: 680 g  
L 5 7/8 x W 5 7/8 x H 3 4/8in

Tala North America, Inc., 2 Research Place,  
Suite 300, Rockville, MD 20850

us.tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

## WARRANTY

2 years

## EAN

5060915712202

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights

# KILTER WALL LIGHT

tala®

SKU: KLT-WL-SB-01-US

FINISH: POLISHED BRASS

The Kilter Wall Light by Tala mounts flush to the wall or ceiling to create a seamless exchange with the environment. The circular solid brass fixture is designed to house Tala's Kilter S14d light sources. IP44 rated for outdoor use.



## PHYSICAL

Sconce:	L 2 1/8 x W 4 2/8 x H 4 2/8in
Not used:	L - x W - x H -in
Cable length:	-
Materials:	Brass
Finish:	Polished Brass
Weight:	1200g
IP rating:	IP44
Base:	S14D

## ELECTRICAL

Appliance class	Class I
Power:	6W MAX
Voltage:	110-120V~
Frequency:	50/60Hz



## DIMMING

Recommended dimmer: Lutron Diva DVELV-300P  
Included Dimmer: N/A  
(For a full list of recommended and compatible dimmers see website)

## LOGISTICAL

Unit Packaging  
PC/Ctn: 1  
Gross weight: 1360 g  
L 5 7/8 x W 5 7/8 x H 3 4/8in

## WARRANTY

2 years

## EAN

5060915713483

Tala Energy Ltd. 25b Vyner Street,  
London, E2 9DG, United Kingdom

Tala North America, Inc., 2 Research Place,  
Suite 300, Rockville, MD 20850

us.tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights

# KILTER WALL LIGHT

tala®

SKU: KLT-WL-WT-01-US

FINISH: WHITE

The Kilter Wall Light by Tala mounts flush to the wall or ceiling to create a seamless exchange with the environment. The circular aluminium shell is designed to house Tala's Kilter S14d light sources. IP44 rated for outdoor use.



## PHYSICAL

Spouce:	L 2 1/8 x W 4 2/8 x H 4 2/8in
Not used:	L - x W - x H -in
Cable length:	-
Materials:	Powder coated aluminium
Finish:	White
Weight:	480g
IP rating:	IP44
Base:	S14D

## ELECTRICAL

Appliance class	Class I
Power:	6W MAX
Voltage:	110-120V~
Frequency:	50/60Hz



## DIMMING

Recommended dimmer: Lutron Diva DVELV-300P  
Included Dimmer: N/A  
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,  
London, E2 9DG, United Kingdom

## LOGISTICAL

Unit Packaging  
PC/Ctn: 1  
Gross weight: 680 g  
L 5 7/8 x W 5 7/8 x H 3 4/8in

Tala North America, Inc., 2 Research Place,  
Suite 300, Rockville, MD 20850

us.tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

## WARRANTY

2 years

## EAN

5060915712196

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights