

KILTER I

6W | 375 lm | 2700K

T30-500-6W-2700K-S14D-FR-120V

Kilter bulb 500mm length 6W 2700K S14D frosted 120V

tala®

The Kilter bulb by Tala is a new take on an architectural lighting staple. Defined by its tubular shape, Kilter achieves consistent light throw and reduce shadowed endpoints while offering Tala's signature dimming characteristics.



PHYSICAL

| | |
|---------------------|----------------|
| Bulb diameter: | 1 1/8in |
| Bulb length: | 19 5/8in |
| Glass shape: | T30 |
| Base: | S14D |
| Materials: | Glass & nickel |
| Glass finish: | Frosted |
| Weight: | 185g |
| Max. working temp.: | -5°C to 40°C |
| IP rating: | IP54 |

ELECTRICAL

| | |
|---------------|------------|
| Power: | 6W |
| Current: | 0.06A |
| Voltage: | 110-120V~ |
| Frequency: | 50/60Hz |
| Power factor: | 0.9 |
| Efficiency: | 63 lm/W |
| Lifetime: | 15,000 hrs |

ILLUMINATION

| | |
|----------------------|--------|
| CCT: | 2700K |
| Lumens: | 375 lm |
| Incandescent equiv.: | 32W |
| Flicker: | <5% |
| Beam angle: | 360° |
| Light source: | LED |
| CRI: | 95Ra |
| R9: | 75 |
| TM30 - Rg | 97 |
| TM30 - Rf | 94 |

IES/LDT photometry files and product photography available on request



DIMMING

Dimmable 0-100%
Recommended dimmer: Lutron Diva DVELV-300P
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

Tala North America, Inc., 2 Research Place,
Suite 300, Rockville, MD 20850

LOGISTICAL

| | |
|-----------------------------|------------------------------|
| Unit Packaging | Outer Carton |
| PC/Ctn: 1 | PC/Ctn: 4 |
| Gross weight: 350 g | Gross weight: 1.7 kg |
| L 22 x W 2 6/8 x H 2 6/8 in | L 22 2/8 x W 11 3/8 x H 3 in |

us.tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

WARRANTY

2 years

EAN

5060915712141

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights

KILTER WALL LIGHT

tala®

SKU: KLT-WL-DG-01-US

FINISH: DARK GREY

The Kilter Wall Light by Tala mounts flush to the wall or ceiling to create a seamless exchange with the environment. The circular aluminium shell is designed to house Tala's Kilter S14d light sources. IP44 rated for outdoor use.



PHYSICAL

| | |
|---------------|-------------------------------|
| Spouce: | L 2 1/8 x W 4 2/8 x H 4 2/8in |
| Not used: | L - x W - x H -in |
| Cable length: | - |
| Materials: | Powder coated aluminium |
| Finish: | Dark Grey |
| Weight: | 480g |
| IP rating: | IP44 |
| Base: | S14D |

ELECTRICAL

| | |
|-----------------|-----------|
| Appliance class | Class I |
| Power: | 6W MAX |
| Voltage: | 110-120V~ |
| Frequency: | 50/60Hz |



DIMMING

Recommended dimmer: Lutron Diva DVELV-300P
Included Dimmer: N/A
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

Tala North America, Inc., 2 Research Place,
Suite 300, Rockville, MD 20850

LOGISTICAL

Unit Packaging
PC/Ctn: 1
Gross weight: 680 g
L 5 7/8 x W 5 7/8 x H 3 4/8in

us.tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

WARRANTY

2 years

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights

EAN

5060915712202

KILTER WALL LIGHT

tala®

SKU: KLT-WL-SB-01-US

FINISH: POLISHED BRASS

The Kilter Wall Light by Tala mounts flush to the wall or ceiling to create a seamless exchange with the environment. The circular solid brass fixture is designed to house Tala's Kilter S14d light sources. IP44 rated for outdoor use.



PHYSICAL

| | |
|---------------|-------------------------------|
| Sconce: | L 2 1/8 x W 4 2/8 x H 4 2/8in |
| Not used: | L - x W - x H -in |
| Cable length: | - |
| Materials: | Brass |
| Finish: | Polished Brass |
| Weight: | 1200g |
| IP rating: | IP44 |
| Base: | S14D |

ELECTRICAL

| | |
|-----------------|-----------|
| Appliance class | Class I |
| Power: | 6W MAX |
| Voltage: | 110-120V~ |
| Frequency: | 50/60Hz |



DIMMING

Recommended dimmer: Lutron Diva DVELV-300P
Included Dimmer: N/A
(For a full list of recommended and compatible dimmers see website)

LOGISTICAL

Unit Packaging
PC/Ctn: 1
Gross weight: 1360 g
L 5 7/8 x W 5 7/8 x H 3 4/8in

WARRANTY

2 years

EAN

5060915713483

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

Tala North America, Inc., 2 Research Place,
Suite 300, Rockville, MD 20850

us.tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights

KILTER WALL LIGHT

tala®

SKU: KLT-WL-WT-01-US

FINISH: WHITE

The Kilter Wall Light by Tala mounts flush to the wall or ceiling to create a seamless exchange with the environment. The circular aluminium shell is designed to house Tala's Kilter S14d light sources. IP44 rated for outdoor use.



PHYSICAL

| | |
|---------------|-------------------------------|
| Spouce: | L 2 1/8 x W 4 2/8 x H 4 2/8in |
| Not used: | L - x W - x H -in |
| Cable length: | - |
| Materials: | Powder coated aluminium |
| Finish: | White |
| Weight: | 480g |
| IP rating: | IP44 |
| Base: | S14D |

ELECTRICAL

| | |
|-----------------|-----------|
| Appliance class | Class I |
| Power: | 6W MAX |
| Voltage: | 110-120V~ |
| Frequency: | 50/60Hz |



DIMMING

Recommended dimmer: Lutron Diva DVELV-300P
Included Dimmer: N/A
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

LOGISTICAL

Unit Packaging
PC/Ctn: 1
Gross weight: 680 g
L 5 7/8 x W 5 7/8 x H 3 4/8in

Tala North America, Inc., 2 Research Place,
Suite 300, Rockville, MD 20850

us.tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

WARRANTY

2 years

EAN

5060915712196

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights