

SPHERE III

7W | 600 lm | 2000-2800K

SPHR-G100-7W-2000-2800K-E26-MP-120V

Sphere Large 7W WoD 2000K to 2800K E26 Matte Porcelain US LED Bulb


Tala's Sphere III offers highly impressive technical qualities alongside a refined visual aesthetic. A design feature to be celebrated, the bulb is characterised by its Dim to Warm and flicker free behaviour, offering warm and ambient light when dimmed down from 100-0%. Fitted with a standard E26 base cap.

tala®



PHYSICAL

Bulb diameter:	3 7/8in
Bulb length:	5 3/8in
Glass shape:	G31
Base:	E26
Materials:	Glass & nickel
Glass finish:	Matte white
Weight:	122g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54




ELECTRICAL

Power:	7W
Current:	0.06A
Voltage:	110-120V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	86 lm/W
Lifetime:	15,000 hrs

ILLUMINATION

CCT:	2000-2800K
Lumens:	600 lm
Incandescent equiv.:	48W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	90
TM30 - Rg	101
TM30 - Rf	95

IES/LDT photometry files and product photography available on request



DIMMING

Dimmable 0-100%
Recommended dimmer: Lutron Diva DVELV-300P
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

Tala North America, Inc., 2 Research Place,
Suite 300, Rockville, MD 20850

LOGISTICAL

Unit Packaging	Outer Carton
PC/Ctn: 1	PC/Ctn: 10
Gross weight: 300	Gross weight: 1.6
L 4 1/8 x W 4 1/8 x H 5 6/8in	L 2 2/8 x W 6 2/8 x H 8 5/8in

us.tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

WARRANTY

2 years

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights

EAN

5060400158713