The classic silhouette of this sleek LED wall sconce makes it suitable for both indoor and outdoor applications. The Bowman's die-cast aluminum body houses a powerful, long-lasting LED light source tightly controlled for down light only, yet supplying significant illumination for even the darkest nights. Available in two sizes and five finishes.

Outstanding protection against the elements:

- Powder coat finishes
- Stainless Steel mounting hardware
- Impact-resistant, UV stabilized frosted acrylic lensing

SPECIFICATIONS

DELIVERED LUMENS	1163	
WATTS	47.2	
VOLTAGE	120V, 277V	
DIMMING	ELV	
LIGHT DISTRIBUTION	Symmetric	
MOUNTING OPTIONS	Downlight	
ССТ	2700K**, 3000K	
CRI	80+	
COLOR BINNING	3 Step	
BUG RATING	B1-U0-G0	
DARK SKY	Compliant	
WET LISTED	IP65	
GENERAL LISTING	ETL	
CALIFORNIA TITLE 24	Can be used to comply with CEC 2019 Title 24 Part 6 for outdoor use. Registration with CEC Appliance Database not required.	
START TEMP	-30°C	
FIELD SERVICEABLE LED	No	
CONSTRUCTION	Aluminum	
HARDWARE	Stainless Steel	
FINISH	Powder Coat	
LED LIFETIME	L70; >60,000 Hours	
WARRANTY*	5 Years	
WEIGHT	3.2 lbs.	

^{*} Visit techlighting.com for specific warranty limitations and details. ** Available in Black and Bronze finish only.



BOWMAN6 shown in black



BOWMAN6 shown in bronze



BOWMAN6 shown in charcoal



BOWMAN6 shown in silver




BOWMAN6 shown in white

ORDERING INFORMATION

PRODUCT	LENGTH	FINISH	LAMP
700WSBOW	6 6"	B BLACK Z BRONZE H CHARCOAL I SILVER W WHITE	-LED827 LED 80 CRI, 2700K 120 -LED827277 LED 80 CRI, 2700K 277 -LED830 LED 80 CRI, 3000K 120 -LED830277 LED 80 CRI, 3000K 277

^{*}AVAILABLE IN BLACK AND BRONZE FINISH ONLY




Bowman 6

PHOTOMETRICS*

*For latest photometrics, please visit www.techlighting.com/OUTDOOR

BOWMAN6

Total Lumen Output: 1163
Total Power: 47.2
Luminaire Efficacy: 24.6
Color Temp: 3000K
CRI: 80+
BUG Rating: B1-U0-G0



PROJECT INFO

FIXTURE TYPE & QUANTITY JOB NAME & INFO NOTES

TECH LIGHTING

Visual Comfort & Co.

(II)

7400 Linder Avenue, Skokie, Illinois 60077 T 847.410.4400