MONORAIL ADJUSTABLE STANDOFF

TECH LIGHTING

PRODUCT FEATURES



LAMPING

It is best used on fairly straight runs with a drop greater than 6". A wire grip allows you to easily shorten or lengthen the cable to size it for use. Use standoff supports every three feet of MonoRail run and at corners. Standoffs can be positioned to cover points where rails are joined.

MonoRail Adjustable Standoff



MonoRail Adjustable Standoff

ORDERING INFORMATION

700MOSADJLENGTH (A)	FINISH	
144"	Z ANTIQUE BRONZE	
3 360"	S SATIN NICKEL	
700MOSADJ		
JOB NAME		
NOTES		
-		_




MONORAIL ADJUSTABLE STANDOFF

TECH LIGHTING

SPECIFICATIONS

HARDWARE MATERIAL		
SHADE MATERIAL		
NET WEIGHT	0.25 lbs	
HEIGHT	4in	
WIDTH	0.7in	
LENGTH	0.7in	
WET LISTED		
DAMP LISTED		
DRY LISTED		
GENERAL LISTING	ETL Listed	
INCLUDES		



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS				
MAX WATTAGE PER BULB				
INPUT VOLTAGE			OV	
DIMMING TYPE*				
ССТ				
CRI				
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				
LAMP SHAPE				
LAMP INCLUDED?			Υ	
WARRANTY**			1 Year	

 $^{* \ \, \}text{Dimming information available at} \, \underline{\text{www.techlighting.com/Downloads\#dimming}}$

T20 / T24 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6.			N/A
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to anc sold in California.	ı		N/A

 $^{^*}$ If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.



^{**} Visit techlighting.com for specific warranty limitations and details.