MONORAIL REMOTE KIT 300W

Installs in an accessible location behind the ceiling or wall. Mounts to a standard 4" junction box. Rail drops 2" from ceiling. Add up to six 50 watt elements or up to eight 35 or 37 watt fixture depending on lamp type.

TECH LIGHTING

PRODUCT FEATURES

- (1) 8' long hand bendable MonoRail
- (2) Sets of End Caps

LAMPING

- (1) Power Transformer of your choice
- (2) Individual Rigid Standoffs (lengths will vary)





MonoRail Remote Kit 300w

Kit 300w Caps



ORDERING INFORMATION

700MOKTA300 FINISH

R AGED BRASS
Z ANTIQUE BRONZE
S SATIN NICKEL

700MOKTA300	
JOB NAME	
NOTES	
•	



MONORAIL REMOTE KIT 300W

TECH LIGHTING

SPECIFICATIONS

HARDWARE MATERIAL		
SHADE MATERIAL		
NET WEIGHT		
HEIGHT	20in	
WIDTH	12in	
LENGTH	12in	
WET LISTED		
DAMP LISTED		
DRY LISTED		
GENERAL LISTING	ETL Listed	
INCLUDES		

LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS				
MAX WATTAGE PER BULB			300W	
INPUT VOLTAGE			120V	
DIMMING TYPE*			ELV	
ССТ				
CRI				
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				
LAMP SHAPE				
LAMP INCLUDED?			Υ	
WARRANTY**			1 Year	

 $^{* \ \, \}text{Dimming information available at} \, \underline{\text{www.techlighting.com/Downloads\#dimming}}$

T20 / T24 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6.			N/A
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.	i		N/A

 $^{^{*}}$ If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.



^{*}Visit techlighting.com for specific warranty limitations and details.