MONORAIL 4" ROUND POWER FEED CANOPY LOW-PROFILE SINGLE-FEED

TECH LIGHTING

PRODUCT FEATURES

LAMPING

It brings power directly above a MonoRail run from a remote transformer (sold separately). The low-voltage leads from the remote transformer are connected to the canopy leads inside the junction box. Compatible with MonoRail 1" Rigid Standoff. Not compatible with Power Extenders nor Power Vault Adapter.

MonoRail 4" Round Power Feed Canopy Low-Profile Single-Feed

MonoRail 4" Round
Power Feed
Canopy Low-Profile
Single-Feed

ORDERING INFORMATION

700MOP4C01 FINISH

Z ANTIQUE BRONZE
S SATIN NICKEL

700MOP4C01 _____

JOB NAME _____

NOTES _____
_____

7400 Linder Avenue, Skokie, IL 60077
T 847.410.4400 | F 847.410.4500 | techlighting.com

SPECIFICATIONS

HARDWARE MATERIAL	
SHADE MATERIAL	
NET WEIGHT	0.48 lbs
HEIGHT	1in
WIDTH	4.5in
LENGTH	4.5in
WET LISTED	
DAMP LISTED	
DRY LISTED	
GENERAL LISTING	ETL Listed
INCLUDES	

4"
102 mm

LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS				
MAX WATTAGE PER BULB				
INPUT VOLTAGE			0V	
DIMMING TYPE*				
CCT				
CRI				
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				
LAMP SHAPE				
LAMP INCLUDED?			Y	
WARRANTY**			1 Year	

* Dimming information available at www.techlighting.com/Downloads#dimming

** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 **Title 24** Part 6.			N/A
This product can be used to comply with California Appliance Efficiency Standards 2016 **Title 20** and may be shipped to and sold in California.			N/A

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.