## MONORAIL 4" ROUND POWER FEED CANOPY TECH LIGHTING SINGLE-FEED

**PRODUCT FEATURES** 



### LAMPING

It brings power to the MonoRail run from a remote transformer (sold separately). The low-voltage leads from the remote transformer are connected to the canopy leads inside the junction box.

MonoRail 4" Round Power Feed Canopy Single-Feed



MonoRail 4" Round Power Feed Canopy Single-Feed

### ORDERING INFORMATION

700MOP4C02SHAPE OR SIZE	FINISH	
4" ROUND	Z ANTIQUE BRONZE	
	S SATIN NICKEL	

700MOP4C02	
JOB NAME	
NOTES	



# MONORAIL 4" ROUND POWER FEED CANOPY SINGLE-FEED

### TECH LIGHTING

### **SPECIFICATIONS**

HARDWARE MATERIAL		
SHADE MATERIAL		
NET WEIGHT	0.95 lbs	
HEIGHT	2in	
WIDTH	4.5in	
LENGTH	4.5in	
WET LISTED		
DAMP LISTED		
DRY LISTED		
GENERAL LISTING	ETL Listed	
INCLUDES		

### LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS				
MAX WATTAGE PER BULB				
INPUT VOLTAGE			OV	
DIMMING TYPE*				
ССТ				
CRI				
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				
LAMP SHAPE				
LAMP INCLUDED?			Υ	
WARRANTY**			1 Year	

<sup>\*</sup> Dimming information available at  $\underline{\text{www.techlighting.com/Downloads\#dimming}}$ 

### T20 / T24 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6.			N/A
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to anc sold in California.	ı		N/A

<sup>\*</sup> If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.



<sup>\*\*</sup> Visit techlighting.com for specific warranty limitations and details.