With its unassuming minimalist profile, The Vex outdoor LED wall sconce features up and down lighting and delivers a wide range of optical control and illumination options in a unique and deceptively simple design. Independent, up and down beam angels from 10° - 120° are achieved with simple tool-free adjustment. Beams can be set symmetric or asymmetric in both directions and are lockable. Angle markers ensure consistent and precise aiming and adjustment from fixture to fixture. Vex is ideal for indoor or outdoor accent lighting, ambient and/or wayfinding applications where beam angle is critical and/or being used to add dramatic effects. For a coordinated look, additional sizes available.

Key features

- Tool-free, independent, up/down beam angle adjustment 10° 120°
- Asymmetric or Symmetric Beam Shaping
- Lockable
- · Angle markers for consistent and precise aiming

SPECIFICATIONS

DELIVERED LUMENS	554.3
WATTS	18.7
VOLTAGE	Universal 120V - 277V
DIMMING	0-10V, ELV, TRAC, CL
LIGHT DISTRIBUTION	Symmetric or Asymmetric depending on barn doors position
MOUNTING OPTIONS	Wall
OPTICS	Adjustable beam spread
ССТ	2700K, 3000K or 4000K
CRI	90+
COLOR BINNING	3-Step
BUG RATING	B0-U3-G0
DARK SKY	Non-Compliant
WET LISTED	IP65
GENERAL LISTING	ETL, ADA
CALIFORNIA TITLE 24	Can be used to comply with CEC 2019 Title 24 Part 6 for outdoor use. Registration with CEC Appliance Database not required.
START TEMP	-30°C
FIELD SERVICEABLE LED	Yes
CONSTRUCTION	Aluminum
HARDWARE	Stainless Steel
FINISH	Powder Coat
LED LIFETIME	L70; >60,000 Hours
WARRANTY*	5 years
WEIGHT	2.4 lbs.



VEX shown in black



VEX shown in charcoal



VEX shown in bronze



VEX shown in white

* Visit techlighting.com for specific warranty limitations and details. Ships with optional acrylic cover for protection against outdoor debris.

ORDERING INFORMATION


PRODUCT	CRI/CCT	LENGTH	FINISH	INPUT VOLTAGE
700OWVEX	927 90 CRI, 270 930 90 CRI, 300 940 90 CRI, 400	DOK	H CHARCC Z BRONZE W WHITE B BLACK	
SHIPS WITH OPTIC	NAL ACRYLIC COVE	R FOR PROTECTION	AGAINST OUTDO	OR DEBRIS.

 $\begin{bmatrix} & & \\ \underline{1}, \underline{4}, \underline{6}^{*}, \underline{4} \\ 117 \text{ mm} \end{bmatrix} \xrightarrow{\underline{1}, \underline{3}, \underline{9}^{*}, \underline{4}} \underbrace{\frac{4}{117 \text{ mm}}}_{\text{SS mm}} \underbrace{ \begin{bmatrix} & 2, 3^{*} \\ 117 \text{ mm} \\ 99 \text{ mm} \end{bmatrix}}_{\text{Vex Wall Sconce}}$

PHOTOMETRICS*

VEX

Total Lumen Output:	554.3
Total Power:	18.7
Luminaire Efficacy:	29.6
Color Temp:	3000K
CRI:	90+
BUG Rating:	B0-U3-G0



PROJECT INFO

FIXTURE TYPE & QUANTITY

JOB NAME & INFO

NOTES

TECH LIGHTING

VISUAL COMFORT & CO.

7400 Linder Avenue, Skokie, Illinois 60077 T 847.410.4400



 \otimes 2020 Tech Lighting, L.L.C. All rights reserved. The "Tech Lighting" graphic is a registered trademark. Tech Lighting reserves the right to change specifications for product improvements without notification.

*For latest photometrics, please visit www.techlighting.com/OUTDOOR