



MT-5LD125 - 1 Light

Tesla LED Multiple Spots

WAC LIGHTING

Responsible Lighting®



PRODUCT DESCRIPTION

High brightness, retractable & adjustable spot light.

FEATURES

- Non-IC rated, airtight housings
- Invisible Trim™ is designed to sit flush with the ceiling for a clean, architectural look
- Spot and Flood beam spreads
- 45° vertical adjustment and 365° horizontal rotation
- Accepts one replacement lens
- 50,000 hour rated life
- 5 year WAC Lighting product warranty

FIXTURE PERFORMANCE

| Model # | Beam | CCT | Watts | Lumens | Efficacy | CRI |
|-----------------|------|-------|-------|--------|-----------|-----|
| MT-5LD125T-S927 | 25° | 2700K | 22.5W | 1095 | 48.5 Lm/W | 90 |
| MT-5LD125T-F927 | 40° | | | 1105 | 49 Lm/W | |
| MT-5LD125T-S27 | 25° | 2700K | 22.5W | 1245 | 55 Lm/W | 85 |
| MT-5LD125T-F27 | 40° | | | 1245 | 55 Lm/W | |
| MT-5LD125T-S930 | 25° | 3000K | 22.5W | 1075 | 48 Lm/W | 90 |
| MT-5LD125T-F930 | 45° | | | 1095 | 48.5 Lm/W | |
| MT-5LD125T-S30 | 25° | 3000K | 22.5W | 1390 | 62 Lm/W | 85 |
| MT-5LD125T-F30 | 45° | | | 1335 | 59 Lm/W | |
| MT-5LD125T-S35 | 25° | 3500K | 22.5W | 1350 | 60 Lm/W | 85 |
| MT-5LD125T-F35 | 40° | | | 1330 | 59 Lm/W | |
| MT-5LD125T-S40 | 25° | 4000K | 22.5W | 1515 | 67 Lm/W | 85 |
| MT-5LD125T-F40 | 40° | | | 1450 | 64 Lm/W | |

TRIM ORDER NUMBER

| Model # | Beam | Color Temp | Rated | Finish |
|-------------|-----------------|---------------------------|--------|----------|
| MT-5LD125T | Trim | S 25° | Non-IC | WT White |
| MT-5LD125TL | Invisible Trim™ | F 40° | | |
| | | 927 2700K (90 CRI) | | |
| | | 27 2700K | | |
| | | 930 3000K (90 CRI) | | |
| | | 30 3000K | | |
| | | 35 3500K | | |
| | | 40 4000K | | |

Example: - - - **WT**

Example: MT-5LD125T-S30-WT

WAC Lighting

www.waclighting.com

Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050

Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760

Phone (800) 526.2588 • Fax (800) 526.2585

Fixture Type:

Catalog Number:

Project:

Location:

SPECIFICATIONS

Construction: Die-cast aluminum heat sink painted white. Trim, housing and junction box are 20 gauge steel. Frame and hanger bars are heavy gauge galvanized steel.

J-Box: Seven knockouts and four Romex® style wiring connectors provided for ease of installation. Rated for branch wiring.

Driver: Universal Input (120V - 277V)

Light Source: High output LED

Dimming: Dim to 10% with electronic low voltage (ELV) dimmer (120V only). 0-10V dimming for 120V and 277V.

Mounting: Supplied with hanger bars, adjustable from 14½"-25" to accommodate various joist construction and grid sizes. Includes butterfly brackets which mount to ½" emt or channel and are vertically adjustable. 6½" x 6½" cutout with trim, 7¾" x 7¾" cutout for Invisible Trim™. See instruction sheet for details on installation using spackle ring. Accommodates surfaces from ½" to 1" thick.

Finish: Abrasion resistant powder coat paint in White (WT).

Standards: ETL & cETL Damp Location listed.

COLOR LENSES LENSES

| Color Lens | LENS-16 |
|------------|---------|
| AMB | Amber |
| BLU | Blue |
| GRN | Green |
| RED | Red |
| YEL | Yellow |

LENSES

| | |
|-------------------------|--------------------|
| Clear Lens | |
| Frosted Lens | LENS-16-CL |
| Spread Lens | LENS-16-FR |
| Beam Soft Lens | LENS-16-SPR |
| Beam Elongating Lens | LENS-16-BSL |
| Infrared Filter Lens | LENS-16-BEL |
| UV/Infrared Filter Lens | LENS-16-IR |
| | LENS-16-UI |

ACCESSORIES

| | |
|------------------|----------------------|
| Honeycomb Louver | LENS-16-HCM |
| Cross Louver | LENS-16-CRL |
| 2" Snoot | LENS-16-SNOOT |

HOUSING ORDER NUMBER

Non-IC Rated, Airtight New Construction

MT-5LD125H-NA

