

INSTALLATION INSTRUCTIONS

Model #72686

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

PREPARING FOR INSTALLATION (Fig. 1)

1. Shut off the power at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts in a clear area. Take care not to misplace any small parts necessary for installation.
3. Pull the black, white and ground wires out of post (A).

CONNECTING THE WIRES (Fig. 2)

4. While supporting the fixture, connect the electrical wires as shown in Fig. 2. making sure that all wire connectors are secured. If your post has a ground wire (green or bare copper), connect the fixture ground wire to it. If not, consult your electrician for proper grounding (Fig.2). After wires are connected, tuck them carefully inside the post cup (A) (not included).

COMPLETING THE INSTALLATION (Fig. 1)

5. Align the lantern (C) with post (A) and secure with screws (B). (Fig.1)
6. At this point, unscrew hex coupling (J) and remove flat washer (H), rubber washer (G), and roof (F). Next, unscrew the ball nuts (D) and remove bracket (E).
7. Install (1) one type A bulb up to 100 watts or CFL or LED equivalent (not included) in accordance with the fixture specification. —DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)
8. Replace the bracket (E) and secure with ball nuts (D). Replace the roof (F), rubber washer (G), flat washer (H), and secure with hex coupling (J). Screw in nipple (K), place cap (L) and cap (M) over nipple (K) and secure with finial (N).

Your installation is now complete. Return power and test the fixture.

“CAUTION-RISK OF FIRE CONSULT A QUALIFIED ELECTRICIAN TO ENSURE CORRECT BRANCH CIRCUIT CONDUCTOR”

ATTENTION – RISQUE D’INCENDIE, CONSULTER UN ÉLECTRICIEN QUALIFIÉ POUR VOUS ASSURER QUE LES CONDUCTEURS DE LA DÉRIVATION SONT ADÉQUATS.

