


# TUBE ARCHITECTURAL DS-WS05

# WAC LIGHTING

## LED Wall Mounts



Fixture Type:

Catalog Number:

Project:

Location:

### PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

### FEATURES

- High performance exterior rated LED wall mount light
- Fixture can install upside down to alter light distribution
- Solid aluminum construction
- 5 year warranty

### SPECIFICATIONS

**Input:** Universal voltage 120V - 277VAC, 50/60Hz  
**Dimming:** Electronic low voltage (ELV) : 100% - 5%  
 0-10V: 100% - 1%  
**Light Source:** High output 3 Step Mac Adam Ellipse COB  
 Rated life of 60,000 hours at L70  
**Finish:** Electrostatically powder coated, white, black, bronze and graphite  
**Standards:** IP65 rated, ETL & cETL wet location listed, Energy Star® 2.2 rated Title 24 JA8-2016 Compliant  
**Operating Temp:** -13°F to 122°F (-25°C to 50°C)

### ORDERING NUMBER

Diameter	Watt	Beam	Beam Angle	Color Temp	CRI	Reference Output <sup>1</sup>	Efficacy (lm/w)	Light Distribution	Finish			
						Lumen	CBCP					
DS-WS05	5" 25W	S Straight up or down	16°	927S	2700K	90	1825	10050	73		<b>BK</b> Black <b>WT</b> White <b>BZ</b> Bronze <b>GH</b> Graphite	
				27S	2700K	85	2190	12057	88			
				930S	3000K	90	1895	10427	76			
				30S	3000K	85	2300	12644	92			
				35S	3500K	85	2350	12937	94			
				40S	4000K	85	2375	13062	95			
	DS-WS0517	5" 17W	N Straight up or down	25°	927S	2700K	90	1810	5280	72		
					27S	2700K	85	2170	6335	87		
					930S	3000K	90	1880	5478	75		
		F Straight up or down	33°	30S	3000K	85	2275	6643	91			
				35S	3500K	85	2330	6797	93			
				40S	4000K	85	2350	6863	94			
		F Away from the wall	N/A	N/A	927A	2700K	90	2000	N/A	80		
					27A	2700K	85	2400	N/A	96		
					930A	3000K	90	2075	N/A	83		
30A	3000K				85	2520	N/A	101				
35A	3500K				85	2575	N/A	103				
40A	4000K				85	2600	N/A	104				
F Towards the wall	N/A	N/A	927B	2700K	90	2000	N/A	80				
			27B	2700K	85	2400	N/A	96				
			930B	3000K	90	2075	N/A	83				
			30B	3000K	85	2520	N/A	101				
			35B	3500K	85	2575	N/A	103				
			40B	4000K	85	2600	N/A	104				

DS-WS05-\_\_\_\_\_ - \_\_\_\_\_

<sup>1</sup>Reference output shows 25W output. Multiply by 0.7 to determine output for 17W combinations.

Example: DS-WS05-F930A-WT

wacighting.com  
 Phone (800) 526.2588  
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
 44 Harbor Park Drive  
 Port Washington, NY 11050

Central Distribution Center  
 1600 Distribution Ct  
 Lithia Springs, GA 30122

Western Distribution Center  
 1750 Archibald Avenue  
 Ontario, CA 91760