

VISUAL COMFORT & Co.

CW1261CH: Small Vanity



Dimensions:

Width: 5.0"
Height: 18.0"
Weight: 6.3 lbs.

Extends: 4.25'
Wire: 8" (color;Black/White)
Mounting Proc.: Screw(s)
Connection: Mounted To Box
Bulb Type: Array
Bulb Type: Integrated
Volts: 120
Watts: 10
Watts Consumed: 10
Watts Rated: 10
Hours Rated: 50000
Lumens: 900
Bulb Temp: 3000 °K
CRI: 90

Bulbs:

1 - LEDIntegrated Array 10.0w Max. 120v included

Features:

- This advanced LED technology is carefully designed and selected to consist of the highest quality LED chipsets for superior performance and reliability.
- Fixture may be mounted horizontal or vertical
- Meets Title 24 energy efficiency standards
- Integrated LED fixtures that meet the high efficacy LED standards set forth in Title 24 and are listed in the California Energy Commission Appliance database.

Collection: Loring

May be mounted vertically or horizontally

ADA compliant

Available in three finish options: Aged Iron shade and Aged Iron finish, Matte White shade and Polished Nickel finish, or Polished Nickel shade and Polished Nickel finish

Assortment includes: four and eight-light chandeliers, a flush mount, floor lamp, pendants, one, two and three-light vanity, and ADA wall sconce.

Damp Rated

UPC #:014817615074

Finish: Chrome (CH)

Material List:

1 Body - Steel - Chrome

Safety Listing:

Safety Listed for Damp Locations

Instruction Sheets:

Trilingual (English, Spanish, and French) (CW1261-CW1271-CW1281)

Shade / Glass / Diffuser Details:

Part	Material	Finish	Quantity	Item Number	Length	Width	Height	Diameter	Fitter Diameter	Shade Top Length	Shade Top Width	Shade Top Diameter
Shade	Glass	White	1			2.69	17.75	2.88				

Backplate / Canopy Details:

Type	Height / Length	Width	Depth	Diameter	Outlet Box Up	Outlet Box Down
Back Plate	18.0	5.0	2.0		9.0	2.5

Shipping Information:

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	Fr. Class	UPS Ship
Individual	CW1261CH	1	014817615074	8.1	23.0	13.3	1.43	8.15	175	Yes
NJ Pallet		50		48.0	40.0	78.0	86.67	407.5		No
NV Pallet		50		48.0	40.0	78.0	86.67	407.5		No