

# BLING MEDIUM SCONCE

VISUAL COMFORT & CO.

## PRODUCT FEATURES

### LAMPING

Rated for (1) 5 watt max. G9 Bi-Pin lamp (Not Included). LED includes 3.8 watt, 319 total delivered lumens, 3000K, LED G9 Bi-Pin lamp. Dimmable with most LED compatible ELV and TRIAC dimmers. Mounts up or down.



Dark Bronze



Dark Bronze



Dark Bronze (3/4 View)



Dark Bronze (Lit)



Dark Bronze (3/4 View Alt)

## ORDERING INFORMATION

CDWS181	FINISH	LAMP
	PZ PLATED DARK BRONZE	NO LAMP -L BI-PIN G9 LED 90 CRI 3000K 120V (T20/T24)

CDWS181 \_\_\_\_\_  
JOB NAME \_\_\_\_\_  
NOTES \_\_\_\_\_  
\_\_\_\_\_




# BLING MEDIUM SCONCE

VISUAL COMFORT & Co.

## SPECIFICATIONS

PRIMARY MATERIAL	Aluminum
SHADE MATERIAL	Aluminum
NET WEIGHT	4.5 lbs
HEIGHT	16in
WIDTH	3.5in
LENGTH	6.4in
MIN. EXTENSION FROM WALL	3.5in
UP LIGHT / DOWN LIGHT / BOTH?	
WET LISTED	
DAMP LISTED	
DRY LISTED	
UP / DOWN	
HORIZONTAL / VERTICAL	
WALL / CEILING MOUNT	
GENERAL LISTING	ETL Listed
ADA COMPLIANT	
INCLUDES	



## LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS	319			
WATTS	3.8			
MAX WATTAGE PER BULB	5W		5W	
	120V ELV, TRIAC			
CCT	3000K			
CRI	90 CRI			
LED LIFETIME				
L70	>25,000			
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE	G9		G9	
LAMP SHAPE	T4		T4	
LAMP INCLUDED?	True		False	
WARRANTY**	1 Year		1 Year	

\* Dimming information available at [www.techlighting.com/Downloads#dimming](http://www.techlighting.com/Downloads#dimming)

\*\* Visit [techlighting.com](http://techlighting.com) for specific warranty limitations and details.

## T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8.		Yes	N/A
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.		Yes	N/A

\* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

