ELLIS 36 BATH VISUAL COMFORT & CO.

PRODUCT FEATURES

- Sleek and stylish contemporary Ellis 36 Bath Bar
- · Available in modern finishes
- Also available as Ellis 36 and Ellis Wall
- Can be mounted vertically or horizontally
- Energy-efficient integrated LED, fully dimmable to create the desired ambiance
- 5-year warranty with integrated LED



LAMPING

LED includes 36 watt, 1995 delivered lumen, 90 CRI, 3000K LED module. Dimmable with most LED compatible ELV and TRIAC dimmers. Mounts vertically or horizontally. ADA compliant.

Satin Nickel



Chrome Satin Nickel Nightshade Black Nightshade Black (Alt)

ORDERING INFORMATION

700BCELI	LENGTH (A)	FINISH	LAMP	
	36 36"	C CHROME	-LED930 LED 90 CRI 3000K 120V	
		B NIGHTSHADE BLACK	-LED930-277 LED 90 CRI 3000K 277V	
		S SATIN NICKEL		


700BCELI

JOB NAME
NOTES



SPECIFICATIONS

PRIMARY MATERIAL	Aluminum
SHADE MATERIAL	Acrylic
NET WEIGHT	4 lbs
HEIGHT	4.3in
WIDTH	4.2in
LENGTH	36in
WET LISTED	
DAMP LISTED	
DRY LISTED	
GENERAL LISTING	ETL Listed
INCLUDES	



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS		1995		
WATTS		36		
MAX WATTAGE PER BULB		36W		
		120V ELV, TRIAC		
		277V 0-10V		
ССТ		3000K		
CRI		90 CRI		
LED LIFETIME				
L70		>50000		
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE		Integrated LED		
LAMP SHAPE		Integrated LED		
LAMP INCLUDED?		True		
WARRANTY**		5 Years		

^{*} Dimming information available at www.techlighting.com/Downloads#dimming ** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6/JA8.	Yes		
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.	N/A		

 $^{^{*}}$ If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

