PRODUCT FEATURES


- · Hand-blown glass manufactured in Italy
- This item is made of natural brass. It is a living finish that will patina and warm with age which adds richness. If it gets an uneven patina or spots, a brass cleaner can restore the finish
- Remote and surface mount driver options available. An optional mud-in canopy kit can be ordered separately in conjunction with the 'Remote' driver option for the most minimal ceiling appearance
- Contact factory for custom configurations
- For minimal ceiling appearance, order the optional mud-in canopy kit in conjunction with the 'Remote' driver. It can be viewed here. techlighting.com/Products/Fixtures/Accessories/Collier-Mud-in-Plate
- Protected by a 5-year warranty. Please visit the "About Us" Page on techlighting.com for more for warranty details. Patent Pending

LAMPING

Includes 39.2 watt, 1413 total delivered lumens, 90 CRI 2700K or 3000K LED modules. Remote dimmable with most LED compatible ELV and TRIAC dimmers. 277V dimmable with 0-10V dimmers. Surface dimmable with ELV and TRIAC dimmers. Remote 120V or 277V. Surface 120V-277V. Can be installed on a sloped ceiling up to 45°.



Natural Brass



ORDERING INFORMATION

SLCH233	COLOR TEMP	FINISH	LAMP
	27 2700K	BZ DARK BRONZE	R REMOTE
	303000K	NB NATURAL BRASS	R-277 REMOTE 277V
		N POLISHED NICKEL	S SURFACE

SLCH233	
JOB NAME	
NOTES	



SURFACE CANOPY

SPECIFICATIONS

PRIMARY MATERIAL	Glass
SHADE MATERIAL	Glass
NET WEIGHT	19 lbs
HEIGHT	89.7in
WIDTH	2.8in
LENGTH	2.8in
UP LIGHT / DOWN LIGHT / BOTH?	
WET LISTED	
DAMP LISTED	
DRY LISTED	
MIN. HANGING HEIGHT	89.7in
MAX HANGING HEIGHT	92.7in
TOTAL CORD LENGTH	
TOTAL STEM LENGTH	
STEM QTY	
SLOPED CEILING ADAPTABLE?	Yes 45° Max
GENERAL LISTING	ETL Listed
INCLUDES	

4.5" 114 mm 136 mm 4.2° 107 mm 20 mm D000000000000 3.2° ∑ 89.7" 2278 mm 2365 mm 2.6" 2.8" 72 mm 64 mm 12" min -78" max 1 12" min -78" max 1 17.8" min -44.7" max 14,4" min -41.3" max

REMOTE CANOPY/MUD PLATE

LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS		1413		
WATTS		39.2		
MAX WATTAGE PER BULB		39.2W		
		120V ELV, TRIAC		
		277V 0-10V		
		Universal 120V-277V ELV, TRIAC		
CCT		2700K		
CCI		3000K		
CRI		90 CRI		
LED LIFETIME				
L70		>50000		
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE		Integrated LED		
LAMP SHAPE		Integrated LED		
LAMP INCLUDED?		True		
WARRANTY**		5 Years		

^{*} Dimming information available at <u>www.techlighting.com/Downloads#dimming</u>

T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6/JA8.	Yes		
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.			

 $^{^{\}star}$ If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.



^{**} Visit techlighting.com for specific warranty limitations and details.