

ASSEMBLY INSTRUCTIONS

Melange Extra Large Floating Disc Linear Chandelier

Item # KW5605

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.


TOOLS REQUIRED (NOT INCLUDED):

Phillips Screwdriver Slotted Screwdriver Wire Cutters
Wire Strippers

1. Carefully remove all parts from the box. Place on a clean, soft surface.
2. Remove mounting plate **(B)** from canopy **(G)** by loosening collar ring **(H)**.
3. Install mounting plate **(B)** to the junction box and secure with mounting screws **(C)**.
4. Feed fixture wires through rod **(N)**, then connect to fixture **(T)** and secure with coupling **(K2)**. Repeat for rod **(L)**, connecting to coupling **(K2)** and securing with coupling **(K1)**.
5. Continue feeding fixture wires through rod **(I)**, collar ring **(H)** and canopy **(G)**.
6. Holding fixture upright slide collar ring **(H)** and canopy **(G)** down rods and rest on top of fixture **(T)**. Then connect rod **(I)** to coupling **(K1)**, securing with swivel ball **(F)**.

NOTE: Slide components down slowly to avoid damages.

7. Hang fixture swivel ball **(F)** to the center of mounting plate **(B)** and secure with screws **(D)** using provided wrench **(E)**. See diagram 1.
8. Cut excess wires, being sure to leave enough to reach the junction box. Separate wires, and strip insulation on each 5/8".
9. Connect fixture neutral wire (black) to the driver output neutral wire (black) using wire nut **(A)**.
10. Connect fixture hot wire (red) to the driver output hot wire (red) using wire nut **(A)**.



ASSEMBLY INSTRUCTIONS

Melange Extra Large Floating Disc Linear Chandelier

Item # KW5605

NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

11. Connect supply ground wire (usually green or bare copper) around the green grounding screw (see diagram 1). Tighten.

NOTE: It is imperative that the fixture is grounded.

12. Connect driver input neutral wire (white) to the supply neutral wire (usually white) using wire nut (A).
13. Connect driver input hot wire (black) to the supply hot wire (usually black) using wire nut (A).

CAUTION: Do not reverse the hot and neutral connections.

14. Make sure all wire connections are tight, then carefully tuck into the junction box.
15. Install canopy (G) to mounting plate (B) and secure with collar ring (H).
16. Install discs (J) to fixture (T) and secure with screws (M).
17. Thread tube (P) to socket (O).

NOTE: Do not over-tighten otherwise glass shade could be damaged.

Care Instructions: Clean only with a soft dry cloth or feather duster. Do Not use abrasive or chemical agents.

