




## ASSEMBLY INSTRUCTIONS

### Hardwire assembly



## Olivier Swing Arm Wall Light

Item #PCD2005

### NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

### TOOLS REQUIRED (NOT INCLUDED):


Phillips Screwdriver

Slotted Screwdriver

1. Carefully remove all parts from the box. Place on a clean, soft surface.
  2. Remove mounting plate (B) from fixture (D) by removing screws (H).
  3. Install mounting plate (B) to the junction box and secure with mounting screws (S).
  4. Remove cord covers and portable cord by loosening the wire nuts.
  5. Insert direct wire plug (X) to the bottom of fixture (D).
  6. Wrap fixture ground wire (bare copper) around the green grounding screw (see diagram 1). Tighten. Continue fixture ground wire and connect to supply ground wire (usually green or bare copper) using wire nut (W).
- NOTE:** It is imperative that the fixture is grounded.
7. Connect fixture neutral wire (white) to the supply neutral wire (usually white) using wire nut (W).
  8. Connect fixture hot wire (black) to the supply hot wire (usually black) using wire nut (W).
- CAUTION:** Do not reverse the hot and neutral connections.
9. Make sure all wire connections are tight, then carefully tuck into the junction box.
  10. Install fixture (D) to mounting plate (B) and secure with screws (H).

## ASSEMBLY INSTRUCTIONS

### Hardwire assembly



## Olivier Swing Arm Wall Light

Item #PCD2005

### NOTICE:

This light fixture should be installed in accordance with all applicable, local installation codes, and by a person familiar with the construction and operation of it, as well as the hazards involved. Inspect item and contents carefully. If any damage or defect is found, do not install. Retain all packaging material until installation is complete and approved.

11. Remove socket ring **(N)** from socket **(M)**, then install harp **(O)** to socket and secure with socket ring **(N)**.
12. Install light bulb into the socket.
13. Remove finial **(Q)** from harp **(O)**.
14. Remove shade **(P)** from packaging, then install shade **(P)** to harp **(O)** using finial **(Q)**.  
**NOTE:** If shade has additional packaging, carefully cut off from interior of shade to avoid damages.
15. Swing arms **(K) & (L)** to desired angle.

**Care Instructions:** Clean only with a soft dry cloth or feather duster. Do not use abrasive or chemical agents.