

Geneva Wall

CV1021, CV1022, CV1023, CV1024 | 1.0

GENERATION LIGHTING WALL

GENERAL PRODUCT INFORMATION:


These fixtures are intended to be installed utilizing NEC compliant junction boxes.

This product is safety listed for damp locations.

This instruction shows a typical installation.

CAUTION - RISK OF FIRE
This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.
Use minimum 90°C supply conductors.


SAVE THESE INSTRUCTIONS!



GENERATION LIGHTING
7400 Linder Ave., Skokie, IL 60077
T 847.410.4400 | F 847.410.4500
www.generationlighting.com

Install the Fixture

IA



- 1 Secure the mounting plate to the junction box.
- 2 **For Models with Short Shade:** Use shade screws and finial to secure short shade. Repeat for remaining short shades.
- 3 Screw the lamp(s) into the socket(s). Refer to the label on the socket for Max Wattage Information.
- 4 Place the long shades onto the socket and secure in place by screwing the collar nut onto the socket using the provided shade tool. Repeat for remaining shades.
- 5 Connect the fixture to a suitable ground in accordance with local electrical codes.
- 6 Connect the white fixture wire to the neutral power line wire with a wire nut.
- 7 Connect the black fixture wire to the hot power line wire with a wire nut.
- 8 Neatly tuck the wiring into the junction box, place the fixture base onto the mounting plate, and secure it in place using fixture screws.