


R2RAT, R2SAT

2" Volta - Adjustable Trim

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Volta LED downlight series represents an innovation in design and technology for architectural lighting. This high lumen and adaptable family of fixtures with a comprehensive set of round and square fittings, affords a sustainable solution for commercial, corporate, and upscale residential applications.

FEATURES

- Center beam alignment retained throughout adjustment range
- 0-45° vertical and 365° horizontal lockable hot aiming
- Indexed vertical scaling for precise and accurate alignment
- Integral patterned tempered trim lens included standard
- Compatible with a wide range of accessories
- Dual finishes are single piece, no physical seams
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast self-flanged aluminum construction

Input: Universal 120 - 277V AC 50/60 Hz

Dimming: Electronic Low Voltage (ELV): 100%-5%
0-10V: 100-0%
Lutron Hi-Lume 1% Ecosystem Fade-to-Black option

Light Source: High output 3-step Mac Adam Ellipse COB
Rated life of 50,000 hours at L70

Mounting: Heavy gauge retention clips support trim firmly. Safety cabling standard.
Ceiling cut out Round Trimmed: Ø 3 3/16" Invisible Trim: Ø 4 1/4"
Ceiling cut out Square Trimmed: 3 3/16" x 3 3/16" Invisible Trim: 4 1/4" x 4 1/4"
Accommodates 1/2" - 1 1/2" ceiling thickness

Finish: Electrostatically powder coated White, Black. Enamel coated Haze. Plated and brushed Copper Bronze.

Standards: ETL & cETL Wet location Listed, Title 24 JA8-2016 Compliant.

Model	Beam	Lumens	BCBP	Reference	Output*	Color Temp	CRI	Finishes	Reflector/Trim
<p>R2RAT Round Trim R2SAT Square Trim</p>	S 12°	Round		335	4300	827 2700K 85	BK Black BKWT Black/White CB Copper Bronze HZ Haze HZWT Haze/White WT White	Reflector/Trim	
		Square		360	5805	830 3000K 85			
	N 25°	Round		915	5340	835 3500K 85			
		Square		1040	5960	840 4000K 85			
	F 35°	Round		940	2910	927 2700K 90			
		Square		1015	3215	930 3000K 90			

R2_AT-_____ - _____

Example: **R2RAT-S827-BK**

*Reference output shows **830**(85CRI 3000K) trim with **22** housing. Use multiplier table below to determine the output for other combinations.

Multiplier	TRIM					
	827	927	830	930	835	840
HOUSING 22	0.95	0.81	1.00	0.86	1.05	1.07
HOUSING 15	0.66	0.56	0.69	0.59	0.72	0.74

Example: **R2SAT-N840-WT** with **15** housing: 1040 lm (Reference Output) x 0.74 (Multiplier) = 770 lm

5960 CBCP (Reference Output) x 0.74 (Multiplier) = 4410 CBCP

Please see next page for housing units(required)

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122



Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

R2RAT, R2SAT

2" Volta - Adjustable Trim

WAC LIGHTING

Responsible Lighting®

HOUSING (Required)	Model	Trim	Power	Driver	Emergency Backup
New Construction Airtight IC 	R2RN Round R2RC Round Chicago Plenum R2SN Square R2SC Square Chicago Plenum	T Trim L Invisible Trim	15 15W IC 22 22W IC	DEFAULT L1 ELV, 0-10V Lutron Hi-Lume 1%	EM Optional
Remodel Non-IC 	R2BR	T Trim	15 15W Non-IC 22 22W Non-IC	DEFAULT ELV, 0-10V	N/A

R2 _____ - _____
 Example: **R2RNT-15** or **R2RNT-15EM** (with Emergency backup battery)

WOOD AND METAL CEILING ADAPTERS

Round	Square
R2R-ADP1 1/2" to 1" ceiling thickness R2R-ADP2 1" to 1 1/2" ceiling thickness	R2S-ADP1 1/2" to 1" ceiling thickness R2S-ADP2 1" to 1 1/2" ceiling thickness

FIELD CHANGEABLE GLARE CONTROL AND OPTIC SYSTEM

Accessory holder
 Holds up to two lenses or one lens and one glare control

Optical cartridge
 Allows tool-less exchange of reflectors



ACCESSORY HOLDER sold separately

LENS-16-HLD	Required for use with any lens or accessory
--------------------	---

GLARE CONTROL ACCESSORIES

LENS-16	HCM Honeycomb Louver CRL Cross Louver
----------------	--

INTERCHANGEABLE REFLECTORS

REF-R2-N	Narrow Flood beam
REF-R2-F	Flood beam
REF-R2-W	Wide beam

LENS ACCESSORIES

LENS-16	AMB Amber RED Red FR Frosted SPR Spread BEL Beam Elongating
----------------	--

wacighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91760