

R4RWT, R4SWT

4.5" Volta - Wallwash Trim

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Volta LED downlight series represents an innovation in design and technology for architectural lighting. This high lumen and adaptable family of fixtures with a comprehensive set of round and square fittings, affords a sustainable solution for commercial, corporate, and upscale residential applications.

FEATURES

- Dual finishes are single piece, no physical seams
- Innovative bi-directional spread lens
- Engineered for even wall illumination both vertically and horizontally
- 5 year WAC Lighting product warranty

SPECIFICATIONS

- Construction:** Durable die-cast self flanged aluminum construction
- Input:** Universal 120 - 277V AC 50/60 Hz
- Dimming:** Electronic Low Voltage (ELV): 100%-5%
0-10V: 100%-0%
Lutron Hi-Lume 1% Ecosystem Fade-to-Black option
- Light Source:** High output 3-step Mac Adam Ellipse COB
Rated life of 50,000 hours at L70
- Mounting:** Heavy gauge retention clips support trim firmly. Safety cabling standard.
Ceiling cut out (Round): Ø 5 1/8"
Ceiling cut out (Square): 5 1/8" x 5 1/8"
Accommodates 1/2"- 1" ceiling thickness
- Finish:** Electrostatically powder coated White, Black. Enamel coated Haze. Plated and brushed copper Bronze.
- Standards:** ETL & cETL Wet location Listed

TRIMS (ORDER HOUSING SEPARATELY)

Model	Beam Angle	Reference Output*		Color Temp	CRI	Finishes	Reflector/Trim
		Lumens	Lumen/Watt				
	R4RWT Round	A Asym	1995	58	827 2700K 85 927 2700K 90 830 3000K 85 930 3000K 90 835 3500K 85 840 4000K 85	BK Black BKWT Black/White CB Copper Bronze HZ Haze HZWT Haze/White WT White	
	R4SWT Square	A Asym	2405	71			

*Reference output shows **830**(85CRI 3000K) trim with **36** housing. Use multiplier table below to determine the output for other combinations.

Multiplier	TRIM					
	827	927	830	930	835	840
HOUSING 36	0.95	0.81	1.00	0.86	1.05	1.07
HOUSING 25	0.66	0.56	0.69	0.59	0.73	0.74
HOUSING 15	0.43	0.37	0.45	0.39	0.48	0.49

R4__WT-_____-_____

Example: **R4RWT-S827-WT**

Please see next page for housing units(required)

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

R4RWT, R4SWT

4.5" Volta - Wallwash Trim

WAC LIGHTING

Responsible Lighting®

HOUSINGS (REQUIRED)


		Model	Power	Rating	Driver	Emergency Backup
	R4RNT Airtight	15 15W 25 25W 36 36W	IC rated IC rated Non-IC	DEFAULT L1	ELV, 0-10V Lutron Hi-Lume 1%	EM
	R4RCT Airtight, Chicago Plenum					
R4SNT Airtight						
	R4SNT Airtight	15 15W 25 23W 36 34W	IC rated IC rated Non-IC	DEFAULT L1	ELV, 0-10V Lutron Hi-Lume 1%	EM
	R4SCT Airtight, Chicago Plenum					
	R4BRT Round or Square					

Field Replaceable Driver

D-R4N-15	Driver for 15W New Construction Hsg
D-R4N-25	Driver for 23W New Construction Hsg
D-R4N-36	Driver for 34W New Construction Hsg

R4 _____ - _____
 Example: **R4RNT-15** or **R4RNT-15EM** (with Emergency backup battery)

BI-DIRECTIONAL SPREAD LENS



AVERAGE WALL ILLUMINANCE*

R4RWT-A830 10' CEILING	ON-CENTER SPACING			
	3'		4'	
	15W	23W	15W	23W
DISTANCE FROM WALL	3'	14 fc	17 fc	11 fc
	3'	22 fc	23W	17 fc
	3'	29 fc	34W	22 fc
DISTANCE FROM WALL	4'	12 fc	15W	9 fc
	4'	18 fc	23W	14 fc
	4'	25 fc	34W	19 fc

R4SWT-A830 10' CEILING	ON-CENTER SPACING			
	3'		4'	
	15W	23W	15W	23W
DISTANCE FROM WALL	3'	16 fc	12 fc	12 fc
	3'	24 fc	23W	18 fc
	3'	32 fc	34W	24 fc
DISTANCE FROM WALL	4'	14 fc	15W	11 fc
	4'	21 fc	23W	16 fc
	4'	28 fc	34W	21 fc

*Results may vary depending on field conditions such as surface properties, ambient light levels, etc.

waclighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91760