

# R2FSA1T

## FQ 2" Shallow - Square Adjustable Trim

# WAC



Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_

### PRODUCT DESCRIPTION

The FQ Recessed series offers a complete line of high performance LED luminaires that provide outstanding functionality and quality. The series features superlative glare control with 30° shielding, 35° vertical tilting and uniform floor-to-ceiling wall washing. Multiple power level options and a full line of round and square, trimmed and trimless luminaires offer versatile solutions for various lighting applications. Easy to order, install, and service.

### FEATURES

- Two-piece die-cast construction, compact size suitable for shallow ceiling plenum
- Light engine mounted on trim with springs for easy replacement
- 0-35° vertical tilting
- Center beam alignment retained throughout adjustment range
- Field changeable beam angle with reflectors provided
- Accepts one Lens or glare control accessory
- 5 year WAC Lighting product warranty

### SPECIFICATIONS

**Construction:** Durable die-cast aluminum construction

**Input** Universal 120-277V AC 50/60 Hz

**Dimming:** Electronic Low Voltage (ELV): 100%-1%  
TRIAC: 100%-1%  
0-10V: 100-1%

**Light Source:** High output 3-step Mac Adam Ellipse COB  
Rated life of 50,000 hours at L70

**Mounting:** Heavy gauge retention clips support trim firmly.  
Safety cabling standard. Ceiling cutout: Ø 3 1/2"  
Accommodates 1/2" - 1" ceiling thickness

**Finish:** Electrostatically powder coated White, Black, Dark Bronze. Enamel coated Haze.

**Standards:** ETL & cETL Damp Location Listed, Energy Star 2.0, Title 24 JA8 Compliant.

Model	Model	Beam	Lumens	CBCP	Color Temp	CRI	Finishes	Reflector/Trim
	<b>R2FSA1T</b> Square Trim	N 25°	1110	2850	<b>927</b> 2700K	90	<b>BK</b> <b>DB</b> <b>HZWT</b> <b>WT</b>	Black Dark Bronze Haze/White White
		F 40°	1100	1855				
		W 55°	1105	1400				
		N 25°	1170	3000	<b>930</b> 3000K	90		
		F 40°	1155	1955				
		W 55°	1165	1470				
		N 25°	1190	3050	<b>935</b> 3500K	90		
		F 40°	1180	1990				
		W 55°	1190	1500				

### R2FSA1T-\_\_-\_\_

Example: **R2FSA1T-927-BK** (Beam N-25° reflector is pre-installed. Beams F-40° and W-55° reflectors are included.)

Please see next page for housing units(required)

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters, East Manufacturing Facility

44 Harbor Park Drive

Port Washington, NY 11050

South East Manufacturing Facility

1600 Distribution Ct

Lithia Springs, GA 30122

Central Manufacturing Facility

1700 South J Elmer Freeway, Ste 100

Cedar Hill, TX 75104

West Manufacturing Facility

1750 S Archibald Ave

Ontario, CA 91761

# R2FSA1T

## FQ 2" Shallow - Square Adjustable Trim



*HOUSING (Required)*

		<i>Model</i>	<i>Power</i>
New Construction IC Airtight		<b>R2FBN1T</b>	<b>1</b> 15W IC
New Construction Frame-in Non-IC		<b>R2FBFT</b>	<b>1</b> 15W Non-IC
Remodel Non-IC		<b>R2FBRT</b>	<b>1</b> 15W Non-IC

**R2FB**\_\_\_\_ - \_\_\_\_

Example: **R2FBN1T-1**

### GLARE CONTROL ACCESSORIES

<b>LENS-11-HCM</b>	<i>Honeycomb Louver</i>
<b>LENS-11P-CRL-BK</b>	<i>Cross Louver</i>

### LENS ACCESSORIES

<b>LENS-11</b>	<b>AMB</b>	<i>Amber</i>
	<b>RED</b>	<i>Red</i>
	<b>BLU</b>	<i>Blue</i>
	<b>GRN</b>	<i>Green</i>
	<b>SPR</b>	<i>Spread</i>
	<b>BEL</b>	<i>Beam Elongating</i>

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters, East Manufacturing Facility

44 Harbor Park Drive

Port Washington, NY 11050

South East Manufacturing Facility

1600 Distribution Ct

Lithia Springs, GA 30122

Central Manufacturing Facility

1700 South J Elmer Freeway, Ste 100

Cedar Hill, TX 75104

West Manufacturing Facility

1750 S Archibald Ave

Ontario, CA 91761