

R2FSD1L-WD

FQ 2" Shallow - Square Downlight Trimless (Dim-To-Warm)



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

The FQ Recessed series offers a complete line of high performance LED luminaires that provide outstanding functionality and quality. The series features superlative glare control with 30° shielding, 35° vertical tilting and uniform floor-to-ceiling wall washing. Multiple power level options and a full line of round and square, trimmed and trimless luminaires offer versatile solutions for various lighting applications. Easy to order, install, and service.

FEATURES

- Two-piece die-cast construction, compact size suitable for shallow ceiling plenum
- Light engine mounted on trim with springs for easy replacement
- 30° shielding angle design for better visual comfort
- Field changeable beam angle with reflectors provided
- Accepts one Lens or glare control accessory
- 5 year WAC Lighting product warranty

SPECIFICATIONS

- Construction:** Durable die-cast aluminum construction
- Input:** Universal 120-277V AC 50/60 Hz
- Dimming:** Electronic Low Voltage (ELV): 100%-1%
TRIAC: 100%-1%
0-10V: 100-1%
- Light Source:** High output 3-step Mac Adam Ellipse COB
Rated life of 50,000 hours at L70
- Mounting:** Heavy gauge retention clips support trim firmly.
Safety cabling standard. Ceiling cutout: Ø 3 1/2"
Accommodates 1/2" - 1" ceiling thickness
- Finish:** Electrostatically powder coated White, Black, Dark Bronze. Enamel coated Haze.
- Standards:** ETL & cETL Wet Location Listed, Energy Star 2.0, Title 24 JA8-2019 Compliant.

| | Model | Beam | Lumens | CBCP | Color Temp | CRI | Finishes | Reflector/Trim |
|--|-----------------------------------|-------|--------|------|-----------------------|-----|--|---------------------------------------|
| | R2FSD1L Square Trimless | F 40° | 980 | 1620 | WD 3000K-1800K | 90 | BK DB HZ WT | Black Dark Bronze Haze White |
| | | W 55° | 970 | 1205 | | | | |

R2FSD1L-WD-__

Example: **R2FSD1L-WD-WT** (Beam F-40° reflector is pre-installed. Beam W-55° reflector is included.)

Please see next page for housing units (required)

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters, East Manufacturing Facility

44 Harbor Park Drive

Port Washington, NY 11050

South East Manufacturing Facility

1600 Distribution Ct

Lithia Springs, GA 30122

Central Manufacturing Facility

1700 South J Elmer Freeway, Ste 100

Cedar Hill, TX 75104

West Manufacturing Facility

1750 S Archibald Ave

Ontario, CA 91761

R2FSD1L-WD

FQ 2" Shallow - Square Downlight Trimless (Dim-To-Warm)



HOUSING (Required)

| | | <i>Model</i> | <i>Power</i> |
|---|--|----------------|---------------------|
| New Construction IC Airtight | | R2FSN1L | 1 15W IC |
| Remodel Non-IC | | R2FSRL | 1 15W Non-IC |

R2FS ___ - ___

Example: **R2FSN1L-1**

GLARE CONTROL ACCESSORIES

| | |
|------------------------|-------------------------|
| LENS-11-HCM | <i>Honeycomb Louver</i> |
| LENS-11P-CRL-BK | <i>Cross Louver</i> |

LENS ACCESSORIES

| | | |
|----------------|------------|------------------------|
| LENS-11 | AMB | <i>Amber</i> |
| | RED | <i>Red</i> |
| | BLU | <i>Blue</i> |
| | GRN | <i>Green</i> |
| | SPR | <i>Spread</i> |
| | BEL | <i>Beam Elongating</i> |

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters, East Manufacturing Facility

44 Harbor Park Drive

Port Washington, NY 11050

South East Manufacturing Facility

1600 Distribution Ct

Lithia Springs, GA 30122

Central Manufacturing Facility

1700 South J Elmer Freeway, Ste 100

Cedar Hill, TX 75104

West Manufacturing Facility

1750 S Archibald Ave

Ontario, CA 91761