

# R1GWT

## Multi Stealth Wall Wash Trim



Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_

### PRODUCT DESCRIPTION

Multi Stealth recessed features a quiet aperture for a nearly glare free environment. Its linear multi cell form factor features a 1.5" aperture, with availability in up to 5 lengths. This series offers a downlight with 40° visual cutoff, an adjustable with 35° bi-directional tilt, and wall washer with specialized optics for even wall illumination. Trimmed and trimless options allow flexibility when integrating to building architecture.

### FEATURES

- Available in 4, 8, and 12 cell configurations
- Provides even illumination on walls with minimal glare
- Interchangeable bevel available in 2 finishes
- Trim flange available in 2 powder coated finishes
- Compatible with R1GNT new construction and R1GRT remodel housings
- Refer to housing instructions for appropriate ceiling cutout dimensions
- 5 year WAC lighting product warranty

### SPECIFICATIONS

- Construction:** Extruded aluminum construction with die-cast end caps.
- Input:** Universal 120-277 VAC 50/60 Hz
- Dimming:** Electronic Low Voltage (ELV), TRIAC: 100%-5%  
0-10V: 100-1%
- Light Source:** High output 3-step Mac Adam Ellipse SMD LED  
Rated life of 50,000 hours at L70
- Mounting:** Heavy gauge retention clips support trim firmly. Safety cabling standard from housing. Accommodates 1/2" to 1 1/2" ceiling thickness. Refer to housing instructions for cutout requirements.
- Finish:** Electrostatically powder coated White, Black trims.  
Injection molded polycarbonate bevels in Black, White
- Standards:** ETL & cETL Damp Location Listed, Title 24 JA8-2019 Compliant.

Model	Size	Beam	Lumens *Ref Output	CBCP *Ref Output	Color Temp	CRI	Finish	Bevel/Flange
R1GWT Wall Wash Trim	04 4 Cell	A Asym	670	N/A	927 930 935 940	90 90 90 90	BKBK BKWT WTWT	Black/Black Black/White White/White
	08 8 Cell	A Asym	1390	N/A				
	12 12 Cell	A Asym	2140	N/A				

### R1GWT -A -BKWT

Example: R1GWT08-A930-BKWT

\*Lumens and CBCP are reference values at 3000K. Use multiplier table below to determine the output for other combinations.

Photometric Multiplier For Multi Stealth	927	930	935	940
	0.95	1.00	1.05	1.07

wacighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760

# R1GWT

## Multi Stealth Wall Wash Trim



HOUSING (Required)		Model	Size	Wattage	Rating	Compatible Trims
<b>New Construction</b> Airtight		<b>R1GNT</b>	<b>04</b> 4 Cell <b>08</b> 8 Cell <b>12</b> 12 Cell	14W 27W 38W	IC IC Non-IC	R1GWT04 R1GWT08 R1GWT12
<b>Remodel</b>		<b>R1GRT</b>	<b>04</b> 4 Cell <b>08</b> 8 Cell <b>12</b> 12 Cell	14W 27W 38W	Non-IC Non-IC Non-IC	R1GWT04 R1GWT08 R1GWT12

**R1GNT**  
 Example: **R1GNT04**