

Sirius

Pendant 3000K

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-81118 18"	3000K	AL Brushed Aluminum BK Brushed Black WT White	35W 36W	2493 1523 2237	1218 466 1109

Example: PD-81118-WT

For custom requests please contact customs@waclighting.com

DESCRIPTION

Full circle. A simple glowing halo completes.

FEATURES

- Up and downlight with recessed silicone diffuser
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Quick spin-on canopy design with minimal hardware for easy installation
- · Can be mounted on slope ceiling
- Driver concealed within the canopy
- 5 year warranty

SPECIFICATIONS

Color Temp: 3000K

Input: 120 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-10%, TRIAC: 100-10%

Rated Life: 50000 Hours

Standards: ETL, cETL,Title 24 JA8 Compliant

Damp Location Listed

Construction: Aluminum body, silicone diffuser

REPLACEMENT PARTS


HDW-SY21-CE - Hardware Pack



FINISHES:



LINE DRAWING:



PD-81118



Sirius

Pendant 3000K

rixture Type.	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-81124 24"	3000K	AL Brushed Aluminum BK Brushed Black WT White	49W 48W	3480 2156 3229	1725 623 1555

Example: PD-81124-WT

For custom requests please contact customs@waclighting.com

DESCRIPTION

Full circle. A simple glowing halo completes.

FEATURES

- Up and downlight with recessed silicone diffuser
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Quick spin-on canopy design with minimal hardware for easy installation
- · Can be mounted on slope ceiling
- Driver concealed within the canopy
- 5 year warranty

SPECIFICATIONS

Color Temp: 3000K

Input: 120 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-10% ,TRIAC: 100-10%

Rated Life: 50000 Hours

Standards: ETL, cETL,Title 24 JA8 Compliant

Damp Location Listed

Construction: Aluminum body, silicone diffuser

REPLACEMENT PARTS


HDW-SY21-CE - Hardware Pack



FINISHES:



LINE DRAWING:





Sirius

Pendant 3000K

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-81131 31"	3000K	AL Brushed Aluminum BK Brushed Black WT White	69W 70W	4763 3285 4606	2054 1139 2024

Example: PD-81131-WT

For custom requests please contact customs@waclighting.com

DESCRIPTION

Full circle. A simple glowing halo completes.

FEATURES

- Up and downlight with recessed silicone diffuser
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Quick spin-on canopy design with minimal hardware for easy installation
- · Can be mounted on slope ceiling
- Driver concealed within the canopy
- 5 Year warranty

SPECIFICATIONS

Color Temp: 3000K

Input: 120 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-10%, TRIAC: 100-10%

Rated Life: 50000 Hours

Standards: ETL, cETL, Title 24 JA8 Compliant

Damp Location Listed

Construction: Aluminum body, silicone diffuser

REPLACEMENT PARTS


HDW-SY21-CE - Hardware Pack



FINISHES:



LINE DRAWING:



PD-81131