



Dra	oct.
FIU	iect:

Location:

Fixture Type:

Catalog Number:

AVAILABLE FINISHES:



Zenith

FM-5415

PRODUCT DESCRIPTION

This diffused, simple, low-profile 15-inch flush mount fixture that is unassuming yet packed with the latest in LED technology. Specify your color temperature for a project and havethe flexibility to select your own in the field with the on-board CCT selection switch. For longer commercial corridors, utilize the unique construction of this flush mount to allow youto seamlessly add in emergency battery backup units, without breaking the size symmetry between fixtures.

FEATURES

- Emergency battery backup option available (special order).
- Driver concealed within the fixture
- Multiple LED array for uniform illumination
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K/5000K

SPECIFICATIONS

Rated Life	60000 Hours

Standards ETL, cETL,Damp Location Listed,Title 24 JA8: 2019 Compliant,Energy

Star 2.0

Input 120-277V,50/60Hz

Dimming ELV: 100-10%,TRIAC: 100-10%

Mounting Can be mounted on ceiling or wall in all orientations

Color Temp 5000K,4000K,3500K,3000K,2700K

CRI 90

Construction Aluminum body with acrylic diffuser

REPLACEMENT PARTS

RPL-SHA-5415 - Shade

Model & Size	Color Temp & CRI	Lumens	Finish	Emergency Backup Battery
	2700K	1663	TT Titanium	Emergency Backup Battery
FM-5415 15"	2700K	1663	TT Titanium	
	3000K	1698	TT Titanium	Emergency Backup Battery
	3000K	1698	TT Titanium	
	3500K	1739	TT Titanium	Emergency Backup Battery
	3500K	1739	TT Titanium	
	4000K	1778	TT Titanium	Emergency Backup Battery
	4000K	1778	TT Titanium	
	5000K	1818	TT Titanium	Emergency Backup Battery
	5000K	1818	TT Titanium	

Example: FM-5415-50-TT-EM

•For emergency battery backup option, add -EM after the finish FM-5415-50-TT-EM

For custom requests please contact customs@modernforms.com