

iQ700, Induction hob, 80 cm, Stainless steel EX879FVC1E



Induction hob with innovative features that enable highly flexible cooking in any situation.

- ✓ Always the optimal cooking zone for your cookware - flexInduction
- ✓ The touchSlider allows the hob temperature to be controlled by entering it directly or by moving the slider with a single finger.
- ✓ fryingSensor: maintains the desired pan temperature automatically after heating up to avoid scorching.
- ✓ Shorter heating times with up to 50% more power thanks to the powerBoost function.
- ✓ Timer with cooking zone shut-off function

Features

Technical Data

Product name/family : Cooking zone ceramic
 Construction type : Built-in
 Energy input : Electric
 Total number of positions that can be used at the same time : 5
 Required niche size for installation (HxWxD) : 51 x 750-780 x 490-500
 Width of the appliance : 812
 Dimensions : 51 x 812 x 520
 Dimensions of the packed product (HxWxD) (mm) : 126 x 953 x 603
 Net weight (kg) : 16.216
 Gross weight (kg) : 17.8
 Residual heat indicator : Separate
 Location of control panel : Hob front
 Color of surface : Stainless steel
 Approval certificates : AENOR, CE
 Length of electrical supply cord (cm) : 110
 EAN code : 4242003717042
 Electrical connection rating (W) : 7400
 Voltage (V) : 220-240
 Frequency (Hz) : 50; 60

Optional accessories

HZ9SE030 : , HZ9LP200 : , HZ9LP160 : , HZ9CF260 : , HZ394301 : ,
 HZ390522 : Griddle Plate , HZ390512 : Teppan Yaki (large) ,
 HZ390230 : , HZ390220 : , HZ390210 : , HZ390012 : , HZ390011 :



iQ700, Induction hob, 80 cm, Stainless steel EX879FVC1E

Features

Control

- touchSlider control
- fryingSensor with 4 temperature settings

Design

- 812 mm
- Side profiles

Special features

- flexInduction zone
- 5 induction cooking zones
- quickStart function
- reStart function
- Timer for all zones
- Acoustic signal
-
- 17 power levels
- Power boost setting
- Energy Consumption Display

Safety Features

- Automatic pan recognition
- Automatic safety switch off
- Control panel lock
- Control panel pause
-
- 2 stage residual heat indicators
- Main on/off switch

Power and size

- Cooking zones: 1 x Ø 180 mm, 1.8 KW (max. Power levels 3.1 KW) Induction; 1 x Ø 145 mm, 1.4 KW (max. Power levels 2.2 KW) Induction; 1 x Ø 240 mm, 2.2 KW (max. Power levels 3.7 KW) Induction; 1 x Ø 400 mmx210 mm, 3.3 KW (max. Power levels 3.7 KW) Induction or 2 x Ø 200 mm, 2.2 KW (max. Power levels 3.7 KW) Induction

Technical information

- Min. worktop thickness: 16 mm
- Connected load: 7.4 KW
- Connection cable 110 cm
- Cable included in packaging

iQ700, Induction hob, 80 cm, Stainless steel EX879FVC1E

Dimensioned drawings

