

KSED65PE

Hood, Decorative wall hood, Universal, Cream, 60 cm, B



TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 60 cm • Extraction: Expulsion • EAN code: 8017709206062

AESTHETICS

Colour: Cream • Aesthetics: Universal • Design: Chimney • Material: Painted material • Type of steel: Brushed

PROGRAMME / FUNCTIONS

No. of speeds: 3

CONTROLS

Control setting: Slider

TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light power: 1 W • Light color temperature scale (°K): 4000 °K • Free outlet maximum capacity: 600 m³/h • Motor power: 200 W • No. of filters: 2 • Anti-grease filters: Aluminium • Minimum distance from GAS hob: 750 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 650 mm • Non return valve: Yes

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): B • Fluid Dynamic Efficiency class (FDEC): B • Grease Filtering Efficiency Class (GFEC): D • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEChood): 60 kWh/year • Fluid Dynamic Efficiency (FDE): 26 • Lighting Efficiency (LE): 100.2 lux/W • Grease Filtering Efficiency (GFE): 74.4 % • Air flow at minimum speed (Qmin): 351 m³/h • Maximum extraction rate: 635 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 53 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 67 dB(A) • Time increase factor (F): 1.1 • Energy Efficiency Index per first cavity: 62.2 • Measured air flow rate at best efficiency point (Qbep): 355 m³/h • Measured air pressure at best efficiency point (Qbep): 385 Pa • Measured electric power input at best efficiency point (Wbep): 146 W • Normal Power of the light system (WL): 2 W • Average illumination of the light on the cooking surface (Emiddle): 221 lux • Sound power level at highest setting (Lwa): 67 dB(A)

ELECTRICAL CONNECTION

Nominal power: 202 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1000 mm

SPEED 1

Extraction rate IEC 61591: 351 m³/h • Noise level IEC 60704-2-13: 53 dB(A) • Power: 140 W

SPEED 2

Extraction rate IEC 61591: 420 m³/h • Noise level IEC 60704-2-13: 57 dB(A) • Power: 157 W

SPEED 3

Extraction rate IEC 61591: 635 m³/h • Noise level IEC 60704-2-13: 67 dB(A) • Power: 191 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 652x600x514 • Width: 600 mm • Depth (mm): 514 mm • Product Height (mm): 652 mm

OPTIONAL

FLT6: Charcoal filter, HoodsKITALLFC: Charcoal filter, Hoods

