


iQ700, Canopy cooker hood, 70 cm, clear glass black printed LB79585MGB

A++



The powerful canopy cooker hood is concealed in a unit above the hob.

- ✓ The quiet high-performance motor: ensures efficient odour and steam removal.
- ✓ LED lights: for optimal visibility and ambience while cooking.
- ✓ Fast-acting extraction for sudden bursts of steam - Intensive Setting

Features

Technical Data

Typology : Traditional
 Approval certificates : CE, VDE
 Length of electrical supply cord (cm) : 150
 Required niche size for installation (HxWxD) : 418mm x 676.0mm x 264mm
 Minimum distance above an electric hob : 500
 Minimum distance above a gas hob : 650
 Net weight (kg) : 9.560
 Type of control : Electronic
 Maximum output air extraction (m3/h) : 575
 Boost position output recirculating (m3/h) : 380.0
 Maximum output recirculating air (m3/h) : 310
 Boost position air extraction (m³/h) : 775
 Number of lights (Stck) : 2
 Noise level (dB(A) re 1 pW) : 64
 Diameter of air outlet (mm) : 120 / 150
 Grease filter material : Washable aluminium
 EAN code : 4242003845530
 Connection rating (W) : 172
 Current (A) : 3
 Voltage (V) : 220-240
 Frequency (Hz) : 50
 Plug type : GB plug
 Installation type : Built-in

Optional accessories

LZ55750
 LZ55651
 LZ11IXC16
 LZ11IXB16
 LZ11ITD11
 LZ10ITP00



iQ700, Canopy cooker hood, 70 cm, clear glass black printed LB79585MGB

Features

Key performance features:

- Energy Efficiency Class: A++ (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use 575 m³/h
- Intensive 775 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 64 dB dB*

Features

- Soft touch button control for extractor speeds and light
- 3 x power levels plus intensive setting
- Automatic intensive revert (6mins)
- 2 x 1W LED lights
- softLight with dimmer function
- Interval operation
- iQDrive motor - efficient BLDC technology
- Automatic after running (30 minutes)
- 2 x metal grease filter cassettes
- Saturation indicator for grease filter

Design

- Canopy hood
- For installation in a kitchen cabinet
- Glass filter cover, Steel filter cover
- Rim ventilation
- Black glass canopy
- Electronic control

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Max. extraction rate: 775 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use: 64 dB(A) re 1 pW
- Intensive: 70 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
- Extraction rate in recirculation mode:
- Max. normal use: 533 m³/h
- Intensive: 722 m³/h
- Noise level in recirculation mode:
- Max. normal use: 71 dB(A) re 1 pW
- Intensive: 77 dB(A) re 1 pW
- Power rating: 172 W
- Light Intensity: 244 lux
- Colour Temperature: 4000 K
- Electrical cable length 1.5 m
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: D*
- Average Energy Consumption: 30.3 kWh/year*
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 418-418 x 700 x 300 mm
- Built-in dimensions (HxWxD): 418 x 676 x 264 mm

Optional accessories

- Recirculating kit LZ10ITP00

* In accordance with the EU-Regulation No 65/2014

iQ700, Canopy cooker hood, 70 cm,
clear glass black printed
LB79585MGB

Dimensioned drawings

