

## iQ700, Island cooker hood, 90 cm, Stainless steel LF91BUV50B



A+



The island hood features a very high extraction rate in a distinguished design that coordinates with a range of Siemens appliances, as well as your kitchen.

- ✓ The quiet high-performance motor: ensures efficient odour and steam removal.
- ✓ cookConnect and climateControl sensor: detects and removes steam and odours automatically
- ✓ Easily control the system with your voice - voiceControl
- ✓ Access and control your hood, no matter where you are - Home Connect App (Android and iOS)
- ✓ Control your system using the Home Connect App - remoteControl.

### Features

#### Technical Data

Typology : Chimney  
 Approval certificates : CE, VDE  
 Length of electrical supply cord (cm) : 130  
 Height of the chimney (mm) : 698-878/698-998  
 Height of product, without chimney (mm) : 46  
 Minimum distance above an electric hob : 550  
 Minimum distance above a gas hob : 650  
 Net weight (kg) : 31.777  
 Type of control : Electronic  
 Number of speed settings : 3-stage + 2 intensive  
 Maximum output air extraction (m<sup>3</sup>/h) : 598  
 Boost position output recirculating (m<sup>3</sup>/h) : 427.0  
 Maximum output recirculating air (m<sup>3</sup>/h) : 359  
 Boost position air extraction (m<sup>3</sup>/h) : 980  
 Number of lights (Stck) : 4  
 Noise level (dB(A) re 1 pW) : 62  
 Diameter of air outlet (mm) : 120 / 150  
 Grease filter material : Washable stainless steel  
 EAN code : 4242003832073  
 Connection rating (W) : 266  
 Current (A) : 10  
 Voltage (V) : 220-240  
 Frequency (Hz) : 50; 60  
 Plug type : GB plug  
 Installation type : Island

### Optional accessories

LZ53850  
 LZ53451  
 LZ31XXB16  
 LZ22CXC56  
 LZ12530  
 LZ12510  
 LZ12410  
 LZ12385  
 LZ12310  
 LZ12285  
 LZ00XXP00



4 242003 832073

## iQ700, Island cooker hood, 90 cm, Stainless steel LF91BUV50B

### Features

#### Key performance features:

- Energy Efficiency Class: A+ (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use 597 m<sup>3</sup>/h
- Intensive 980 m<sup>3</sup>/h
- Noise max. Normal Level: Noise, max. speed in normal us: 62 dB dB\*

#### Home Connect: Remote Monitoring and Control

- Home Connect: Remote Monitoring and Control for connected home appliances and operation via smartphone or tablet (only in countries where Home Connect service is available)
- The Home Connect functionality can be extended by integrating numerous applications from external cooperation partners (partnerships)
- Voice Control enabled via popular voice assistants (only in countries where this service is available)
- Interval function: available via Home Connect
- Silence function: available via Home Connect

#### Features

- touchControl with 7-segment display
- 3 power levels and 2 intensive settings
- Automatic intensive revert (6mins)
- cookConnect hob based hood control
- climateControl sensor
- Fully automatic hood
- softLight with dimmer function
- 4 x 1.5W LED
- Additional noise reduction insulation
- Efficient BLDC motor
- Twin channel high performance fan motor
- Automatic after running (Automatic after running (10 minutes))
- Grease and charcoal filter saturation indicators
- 3 x metal grease filter cassettes - dishwasher safe
- Steel filter cover

#### Design

- Stainless Steel
- For ceiling mounted installation
- Electronic control

#### Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Max. extraction rate: 980 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use: 62 dB(A) re 1 pW
- Intensive: 73 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
- Extraction rate in recirculation mode:
- Max. normal use: 462 m<sup>3</sup>/h
- Intensive: 561 m<sup>3</sup>/h
- Noise level in recirculation mode:
- Max. normal use: 68 dB(A) re 1 pW

- Intensive: 72 dB(A) re 1 pW
- Power rating: 266 W
- Light Intensity: 411 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 744-924 x 898 x 600 mm
- Dimensions recirculating, chimney (HxWxD): 744-1044 x 898 x 600 mm
- 
- Blower Efficiency Class: A\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: B\*
- Average Energy Consumption: 36.8 kWh/year\*

#### Optional accessories

- Recirculating kit LZ00XXP00

\* In accordance with the EU-Regulation No 65/2014

**iQ700, Island cooker hood, 90 cm,  
Stainless steel  
LF91BUV50B**

Dimensioned drawings

